





For Non-Dry Dock Stormwater Monitoring Conducted at Puget Sound Naval Shipyard Bremerton, WA Project ENVVEST Study Area

December 16, 2012



PNNL Contract No.: N4523A10MP00034 Amendment 2





1.0 Introduction

Cardno TEC conducted non-dry dock stormwater sampling event tasks within the Puget Sound Naval Shipyard (PSNS) and adjacent areas within Naval Base Kitsap (NBK); collectively comprising the Project ENVVEST study area, between December 14th and 17th 2012. This was the first of three scheduled events for the 2012-2013 project year – referred to hereafter as *Phase III*. Overall, this was the thirteenth stormwater (SW13) sampling event of the project. A summary of the preparatory and sampling event tasks, including site specific conditions, that occurred during SW13 are presented in this report, with supporting information as attachments.

This SW13 Report is organized in the following manner and contains: <u>Section 2</u>, Phase III Preparatory Tasks; <u>Section 3</u>, SW13 Event Summary; <u>Section 4</u>, Project Staff Participating in SW13; <u>Section 5</u>, Storm Event SW13 Preparatory Tasks; <u>Section 6</u>, Weather Forecast Information; <u>Section 7</u>, Event Targeting, Precipitation Summary and SW13 Qualification; <u>Section 8</u>, Sampling Information, Management and Validation; <u>Section 9</u>, Basin Runoff Calculations; <u>Section 10</u>, Descriptive Statistics and Discussion of Event Station Monitoring Data; <u>Section 11</u>, Telemetry Data Summary Report; <u>Section 12</u>, Notable Field Anomalies and Variations to the 2012-13 PWPA; and <u>Section 13</u>, Action Items.

Attachments to this report include: Table A-1, *Storm Event Summary and Sampling Information, Validation Checklist* (spreadsheet); Storm Event Controller Notes and Stormwater Field Sampling Forms; Chain of Custody Forms; (basin) Runoff Calculation Worksheet; Station Hydrographs; Autosampler Reports and Weather Forecast Information.

2.0 Phase III Preparatory Tasks

At the conclusion of Phase II, several demobilization tasks were conducted as necessary and in preparation for continued future stormwater sampling events. These demobilization tasks included the following:

- Demobilization of all transducers (except from PSNS015), multimeters, autosamplers and batteries from the field (April/May 2012),
- Calibration checks of all current and reserve station (Isco) rain gauges (late May/early June 2012),
- Refurbishment / calibration of select rain gauges by the manufacturer (June/July 2012),
- Station maintenance visits (June/August 2012), and
- Station equipment enclosure re-location, general housekeeping and inventory tasks (early Fall 2012).

Site visits and initial monitoring station setup planning and field tasks began in early October, 2012. By mid-November five out of six Phase III monitoring stations (PSNS015, PSNS053, PSNS084.1, PSNS115.1 and PSNS126) had been either reinstalled or newly installed and were fully operational. The monitoring station PSNSPB01, located at the Pier B Quay Wall water quality treatment system, remained essentially "off-line" until early December - when it was fully installed

and made operational. This delay in setup was due to access constraints and monitoring system configuration issues. A Sample Collection Event Kick-off meeting was conducted on 03 December. This meeting was attended by the Navy and Cardno TEC, with the purpose to review the Phase III station setups, discuss their particulars and to complete site visits. By 10 December, 2012 all six Phase III monitoring stations were fully operational and ready for stormwater collection. Figure 1 shows the general location of the PSNS and NBK monitoring sites.

Between 02 and 05 November, 2012 field equipment blanks were collected at each of the six monitoring stations. Teflon®-lined polyethylene sampling lines coupled with platinum-cured Tygon® Isco autosampler pump head tubing, at each monitoring station, was thoroughly back flushed with laboratory supplied DI water prior to and immediately after field blank collection. Sampling lines at each station were made ready for storm event sample collection. An equipment blank, using the same batch of laboratory supplied DI water, was also collected from a representative stainless steel dip-cup used for grab-style parameter (total petroleum hydrocarbon) collection.

3.0 SW13 Event Summary

Main SW13 details are provided below as a "Quick Reference":

- Event/s Conducted: SW13
- Event Date/s: maint. items; 12/10 through 12/13/12, station prep.; 12/14 and 12/15/12; and storm event tasks occurred between 12/16 and 12/17/12
- Monitoring Stations Sampled: PSNS015, -053, -PB01, -84.1, -115.1 and -126
- Antecedent Conditions Met?: the 24-hr Conditional antecedent (≤20% of total rainfall) was met at all stations except -PB01 (additional 9.5%); the 6-hr antecedent (0.00" preceding the storm/sampling event) was met at all of the stations.
- Start of Rainfall at PSNS Stations: 12/16/12 between (1015) @ PSNS126 and (1110) @ PSNS115.1
- <u>Sampling Period Duration Range:</u> start = 12/16/12 (1049) @ PSNSPB01 and stop = 12/17/12 (1018) @ PSNSPB01. Max sampling duration = 23 hrs:29 mins @ PSNSPB01
- <u>Sampling Event Rainfall Total:</u> PSNSB427 = 1.52", PSNS126 = 1.04", PSNS115.1 = NA, PSNS084.1 = 1.25", PSNS053 = 1.40", PSNS015 = 1.49 and PSNSPB01 = 1.42"
- <u>Samples/Types Collected:</u> Composite samples were collected at all stations, except for PSNS115.1, for a total of 5 "normal" samples. No grab samples collected.
- Quality Control (QC) Samples Collected: One composite (PSNS084.1) duplicate sample was collected during SW13.
- <u>Based on consideration of storm event and sample validation information, were the samples collected during SW13 valid for project purposes? (Y / N, composite, grab or both):</u> Yes, all composite samples collected during this event were valid.

See Table A-1; Storm Event Summary and Sampling Information, Validation Checklist, for additional event summary details.

4.0 Project Staff Participating in SW13

CardnoTEC:

Dave Metallo - Project Manager, Storm Controller, Field Event and QC Manager

Brian Rupert - Field Team Leader

Ian Sahlberg – Field Team Member

Navy Personnel:

Bob Johnston – Project Technical Lead / Oversight / Grab sample collection lead

5.0 Storm Event SW13 Preparatory Tasks

By December 15th, 2012 all six Phase III stormwater monitoring stations (PSNS015, PSNS053, PSNSPB01, PSNS084.1, PSNS115.1 and PSNS126) were initially set up for and readied for storm event / stormwater sample collection. At the time of the initial station setups all of the monitoring equipment was deemed to be functioning properly, was operational and "sample ready" (see Sections 1 and 2 of the attached *Stormwater Field Sampling Forms*).

All stations were programmed with pre-determined autosampler enable and pacing conditions set "high" to prevent premature enabling (*sample disable mode*). Station operation was passed to the CardnoTEC Storm Controller to be managed via telemetry. Final enabling conditions were determined by the Storm Controller closer to the onset of the storm event. See the *Storm Control Worksheet* for details.

6.0 Weather Forecast Information

The Nation Weather System (NWS) was one of the main sources used for the assessment of weather forecasting and conditions. Provided below is a link to the NWS-Bremerton, WA webpage; (http://forecast.weather.gov/MapClick.php?site=sew&textField1=47.56751&textField2=-122.63127&smap=1). A host of other internet available weather forecasting, observational and data sources were used for field and reporting purposes as appropriate. Detailed *Weather Forecast Information* is attached to this report.

Routinely referenced weather models used to gain forecast information regarding the Pacific Northwest included the MM5-NAM http://www.atmos.washington.edu/mm5rt/rt/naminit.12km.html) and the GFS-WRF (http://www.atmos.washington.edu/mm5rt/rt/gfsinit.frame1.html) (both hosted by the University of WA and initialized for the PNW). Below is a synopsis of the model comparison for SW13:

"Model predictions (GFS and NAM) are showing rain arriving between 10 (NAM) and 1400 (GFS) on 12/16/12. The GFS has rain becoming heavy throughout most of the day and night into the early morning hours, finally tampering off in the mid-morning hours, with passing bands and periods of no rain until 1400 Monday, with totals around 1.75". The NAM shows heavy rain from 1000 to about 2000, then lighter rain until around midnight Sunday 12/16/12, tampering to little to

no rain until mid-morning morning Monday 12/17 when passing bands return to add to a little more depth to the total of about 1.5".

A potentially qualifying storm event (event probability and forecast rainfall depth) was identified and targeted for 12/16/12. Rain was forecast at between 90% to 100% probability for Sunday 12/16/12, with 24-hour accumulations of between 1.02" (NWS) to 1.75" (GFS) into late morning of Monday the 17th.

The NWS synopsis for the approaching event was as follows: A strong pacific storm will race toward the area today (Sunday). This system will bring the potential for damaging winds across the Lowlands and heavy snow to the mountains tonight and Monday. Look For showery weather to prevail in the wake of the occluded front that will move across the region Monday morning. The snow levels will also fall to near sea level Monday night as a colder air mass settles over the area. Higher pressure aloft will slowly build in from the west during the day Tuesday.

Based on the weather forecast information available, as summarized above, the decision was made by the Navy to continue preparing for stormwater sample collection. The CardnoTEC Storm Controller coordinated with internal staff, PNNL and Navy personnel regarding schedule, grab and composite collection and post-event tasks. The antecedent dry period continued to be monitored and the sampler enabling conditions were appropriately set.

7.0 Event Targeting, Precipitation Summary and SW13 Qualification

Event Targeting:

Final sampler enabling conditions were appropriately set at each monitoring station between (2342) on the 15th and (1216) on the 16th (*sample ready mode*). Table 1 lists the final enabling conditions at each monitoring station that were used for SW13.

Table 1. Monitoring Station Enabling Conditions

| Station | Rainfall (in/hr) | Level (ft) | Conductivity (μS/cm) | Repeatable Enable (Y/N) | Pacing (min) |
|-----------|------------------|------------|-------------------------|----------------------------|--------------|
| PSNS126 | 0.05 | 0.3 | 2000 | N | 15 |
| PSNS115.1 | 0.05 | 0.3 | 2000 | Y-cond | 15 |
| PSNS084.1 | 0.05 | 0.3 | 2000 | N | 15 |
| PSNS053 | 0.05 | 0.3 | 2000 | N | 15 |
| PSNS015 | 0.05 | 0.3 | 2000 | N | 15 |
| PSNSPB01 | 0.05 | 0.24 | NA | Y-level | 15 |

1 Conditions as checked at (0900-1205) on 12/16/12; final enable conditions set at ~(0000) on 12/15/12

Precipitation Summary:

Between December 10th (all stations fully operational) and just prior to the onset of SW13 (12/16/12 @ 1015) the average rainfall as measured at the six monitoring stations during this approximately 6 day period was 0.62". The Navy's rain gauge at Build 427 recorded a total of 0.63" during the same period.

Previous rainfall that caused runoff to occur (≥ 0.03" rainfall without 3-hr gap) prior to the onset of SW13 ranged from 18 hours at PSNS053 to 20 hours at PSNS115.1 and PSNS084.1. These rainfall amounts were measured by each stations rain gauge.

The project defined qualifying antecedent dry period (≤0.1" rainfall in 24-hrs prior to storm event) was not met at any of the stations prior to the onset of SW13. However, the 6-hr antecedent condition (0.00" of rainfall) was met at all of the stations. Upon examination of the post-event rainfall data it was determined that five of the six stations met the conditional antecedent dry period (≤20% of the total event rainfall in prior 24-hrs), with PSNSPB01 being the exception at with an 9.5% overage.

Rain began to fall over the project site between 1015 (PSNS126) and 1110 (PSNS115.1) on December 16th. Table 2 details the period since last runoff, antecedent duration prior to the start of the storm event, rainfall amounts in the 24 and 6 hour periods prior to the event start, as well as the rainfall start date/time at each monitoring station.

Table 2. Pre-Rain Event Conditions

| Station | Last Runoff ¹ (Date/Time) | Antecedent Dry Period (Days: Hrs) | Rainfall Prior 24-hrs to Rain Event Start (in) | Rainfall Prior 6-hrs to Rain Event Start (in) | Start of Rainfall (Date/Time) |
|-----------|---|---|--|---|----------------------------------|
| PSNS126 | 12/15/12 15:10 | 0:19 | 0.23 | 0.00 | 12/16/12 10:15 |
| PSNS115.1 | 12/15/12 15:25 | 0:20 | 0.22 | 0.00 | 12/16/12 11:10 |
| PSNS084.1 | 12/15/12 15:25 | 0:20 | 0.26 | 0.00 | 12/16/12 10:50 |
| PSNS053 | 12/15/12 16:00 | 0:18 | 0.31 | 0.00 | 12/16/12 10:20 |
| PSNS015 | 12/15/12 15:45 | 0:19 | 0.31 | 0.00 | 12/16/12 10:20 |
| PSNSPB01 | 12/15/12 15:55 | 0:19 | 0.42 | 0.00 | 12/16/12 10:30 |

¹Last runoff period is defined as ≥ 0.03" of rainfall without a 3-hr gap

Operational checks via telemetry throughout the day and evening of December 16th and the morning of the 17th revealed that all of the stations enabled their sampling routines as programmed; with rainfall, pipe level and conductivity values being in satisfaction of their threshold values, (as listed in Table 1).

Station sampling period rainfall totals ranged from 1.04" at PSNS126 to 1.49" at PSNS015. The Navy's rain gauge at B427 recorded 1.52" over the entire combined length of the sampling period for all project monitoring stations.

Sampling routines at all of the stations were manually stopped via telemetry on the morning of the December 17th, as the storm event was over and runoff and/or tidal influences had returned to non-rain conditions. Sampling durations (the range of time covering bottles used in the formulation of the overall station composite sample) ranged from 11:44(hrs:mins) at PSNS084.1 to 23:29(hrs:mins) at PSNSPB01.

Table 3 summarizes the sampling period start, sampling period end, sampling period duration, as well as the total rainfall amounts for each monitoring station and the PSNS project rain gauge at B427. Rainfall amounts listed occurred during the station's sampling period associated with SW13. Table A-1 (*Storm Event Summary and Sampling Information, Validation Checklist*), attached to this report, provides additional sampling period rainfall information.

Table 3. Sampling Period Information and Rainfall Totals for Project Monitoring Stations

| Station | Sampling Period Start (Date/Time) | Sampling Period End (Date/Time) | Sampling Period Duration (Hrs:Mins) | Total Sampling Period Rainfall (in) |
|------------------------|--------------------------------------|------------------------------------|---|---|
| PSNS126 | 12/16/12 14:16 | 12/17/2012 5:00 | 14:44 | 1.04 |
| ¹ PSNS115.1 | NA | NA | NA | NA |
| PSNS084.1 | 12/16/12 14:59 | 12/17/2012 2:43 | 11:44 | 1.25 |
| PSNS053 | 12/16/12 14:36 | 12/17/2012 6:20 | 15:44 | 1.40 |
| PSNS015 | 12/16/12 13:20 | 12/17/2012 5:04 | 15:44 | 1.49 |
| PSNSPB01 | 12/16/12 10:49 | 12/17/2012 10:18 | 23:29 | 1.42 |
| ² B427 | 12/16/12 10:49 | 12/17/2012 10:18 | 23:29 | 1.52 |

¹Programming/communication issue prevented sampler at PSNS115.1 from enabling and collecting samples

SW11 Qualification Summary:

All storm qualification conditions were met for this event. Storm event qualification conditions included wet season event date range (Oct 1 − May 1), forecast probability (≥70%), forecasted storm depth (≥0.1"), storm duration (≥2hrs) and runoff occurrence / hydrograph stage (elevated above base flow). Antecedent dry period (≤0.1" rain in previous 24hrs and 0" rain in previous 6hrs) qualification for SW13 was conditionally met, as detailed above, except at PSNSPB01. However, due to the "flashy" nature of the drainage basin and the unique structure of this outfall (water quality treatment system), the Navy decided that samples from PB01 would be acceptable from this event. Table A-1 (*Storm Event Summary and Sampling Information, Validation Checklist*), documents the particular SW13 qualification criteria listed above.

²B427 start/stop and duration incorporates the total span from all monitoring stations

8.0 Sampling Information, Management and Validation

Grab Sampling:

No grab samples were collected during this event.

Table 4. Grab Sampling Information

| Sample Collection Criteria: | PSNS126 | PSNS115.1 | PSNS084.1 | PSNS053 | PSNS015 | PSNSPB01 |
|---|---------|-----------|-----------|---------|---------|----------|
| Grab sample ID | N/A | N/A | N/A | N/A | N/A | N/A |
| Grab Date /Time | N/A | N/A | N/A | N/A | N/A | N/A |
| Grab sample conductivity value (μS/cm) | N/A | N/A | N/A | N/A | N/A | N/A |
| Hydrograph stage at grab collection | N/A | N/A | N/A | N/A | N/A | N/A |
| Grab parameters collected per PSNS PWP? | N/A | N/A | N/A | N/A | N/A | N/A |

Composite Sampling:

Composite sample retrieval tasks and formulation procedures were managed and lead by CardnoTEC with support from PNNL/MSL personnel as needed. Composite samples were collected from five of the six monitoring stations - PSNS115.1 being the exception.

Composite samples were collected via autosamplers which were operated and synchronized by a custom designed telemetered water quality control system. The composite sample collection period and duration for each monitoring station is noted in Table 3.

Discrete sample (wedge) bottles from each station (contained in the autosampler bases) were brought back the C106 Stormwater Lab at B147 for processing. Composite formulation occurred on December 17th between 1230 and 1545. The numeric identification and amount of wedge bottles that were used for the composite sample formulation and those that were discarded were noted in Section 5 of the attached *Stormwater Field Sampling Forms*.

Methods used in preparation, autosampler collection, retrieval and formulation of the composite samples were conducted in a routine manner as per the 2012-13 PWPA. Samplers at each station were enabled as per the conditions stated in Section 7 of this report. Composite sample parameters included: hardness, TOC, DOC, TSS, total metals, dissolved metals, conductivity and turbidity.

The total number of discrete wedge bottles collected at each sampler, along with the total number of those bottles used in the station's composite sample is noted below in Table 5. Dividing the number of wedge bottles used in the composite sample formulation by the total number of wedge

bottles collected during the span of the entire sampling period provides an estimation of the amount of time (as a percentage of that stations entire collection period) where freshwater (i.e. runoff) conditions occurred at each station during the corresponding sampling event period.

Specific details regarding the composite formulation, results from individual bench top testing of the discrete bottles, sample IDs, sample date/time and resultant overall conductivity and turbidity values, as well as the number of wedge bottles collected during the sampling event and those used for the composite sample formulation are detailed in the *Stormwater Field Sampling Forms, Chain-of-Custody (CoC)* forms and in Table A-1 (all are attached). Table 5 summarizes these results.

Table 5. Composite Sampling Details

| Sample Collection Criteria: | PSNS126 | PSNS115.1 | PSNS084.1 | PSNS053 | PSNS015 | PSNSPB01 |
|--|--------------------|-----------|--------------------|--------------------|--------------------|---------------------|
| Composite sample ID | SW13-0001 | N/A | SW13-0002 | SW13-0006 | SW13-0005 | SW13-0004 |
| Composite Date /Time | 12/17/2012 5:00 | N/A | 12/17/2012 2:43 | 12/17/2012 6:20 | 12/17/2012 5:04 | 12/17/2012 10:18 |
| Overall Composite conductivity value (µS/cm) | 330 | N/A | 231 | 84 | 228 | 51 |
| Overall Composite turbidity value (NTU) | 3 | N/A | 8 | 7 | 14 | 5 |
| Composite volume (ml) | 6,000 | N/A | 5,250 | 6,000 | 6,400 | 7,200 |
| Number of Bottles Collected During Sampling Event | 22 | N/A | 11 (22hr span) | 20 | 21 | 24 |
| Number of Bottles Included in Composite Sample | 15 | N/A | 6 (12hr span) | 15 | 16 | 24 |
| Percentage of Total Sampling Period that Freshwater Conditions Occurred | 68% | N/A | 55% | 75% | 76% | 100% |
| Composite parameters collected per PSNS PWP? | Yes | N/A | Yes | Yes | Yes | Yes |

All sampling and vault monitoring equipment operated as designed and programmed - except for PSNS115.1. Details pertaining to autosampler programming and event-specific operation of each monitoring stations' autosampler unit are contained in the attached *Sampler Reports*. The anomaly at PSNS115.1 is further explained in Section 11 of this report.

QC Samples:

During SW13 one composite duplicate sample was collected at PSNS084.1. As mentioned in Section 2, field equipment blanks were collected at each monitoring station (and from representative grab sampling equipment) prior to the SW13 storm sampling event. These are the only planned equipment blanks that will be collected for the 2012-13 Phase III sampling events. Equipment blank identification information is listed in Table A-1. Table 6 summarizes the quality control sample collection information for SW13.

Table 6. Summary of Quality Control Sampling Information for SW13

| Sample Collection Criteria: | PSNS084.1 |
|--|-----------------|
| Grab sample duplicate ID | |
| Grab sample duplicate date and time | |
| Grab sample duplicate conductivity value (μS/cm) | |
| Composite sample Duplicate ID | SW13-0003 |
| Composite sample duplicate date and time | 12/17/2012 2:43 |
| Overall Composite Duplicate conductivity value (µS/cm) | 315 |
| Overall Composite Duplicate turbidity value (NTU) | 8 |
| Composite Duplicate volume (ml) | 5,250 |

Sample Management:

All samples were handled and managed as per Section 9 of the 2012-13 PWPA and in a manner acceptable and within industry standards regarding practices typical for tasks of this nature. Once collected, both grab and composite samples were placed into coolers and put on ice and/or into the secure Stormwater Laboratory refrigerator to maintain temperatures between 2 and 6 °C.

All sample IDs, collection date and time, matrix, requested parameter analysis and other associated information were documented on *Chain of Custody (CoC) Forms* (attached). Samples were in direct control of project and/or laboratory personnel at all times. Samples were delivered to the testing facility, Battelle Marine Science - Pacific Northwest National Laboratory in Sequim, WA, in good, useable and properly chilled condition. Adequate sample volume was collected from the targeted stations to proceed with the scheduled analysis of all parameters per the 2012-13 PWPA.

Sample Validation Summary:

All sample validation criteria were met for this event per Section 8.2.6 of the 2012-13 PWPA. Prior to processing the samples and transferring custody to the analytical laboratory, the CardnoTEC Field Event Lead validated the samples against certain criteria. These validation criteria included runoff occurrence / hydrograph stage, sample preparation and handling review, requested parameters, ≥2 hour sampling duration or 75% storm hydrograph coverage, minimum number of

aliquots, minimum sample volume collected for required parameters, discrete and composite samples conductivity measurement results, quality control sample collection and anomalous conditions assessment. Table A-1 (*Storm Event Summary and Sampling Information, Validation Checklist*), documents the particular SW-event qualification listed above.

9.0 Basin Runoff Calculations

Rainfall runoff volumes during the SW13 sampling period were calculated for each of the basins associated with the six Phase III monitoring stations. These calculations are based on the modified Runoff Coefficient Method (RCM) as described in Section 7.4 of the 2012-13 PWPA.

The value ranges for the various land use/land cover categories assigned to each basin are listed in the attached *Runoff Calculation Tables*. Calculated runoff values are also presented in Table A-1 (*Storm Qualification and Sample Validation Information Checklist*) (attached). Table 7 summarizes the results from these calculations.

Table 7. Runoff Calculations for SW13

| Station | Type of Surface | Area of Basin Surface Type (ft²) | ¹ Runoff Coefficient Range | Combined Drainage Area (Ft ²) | Sample Event Rain Total (In) | Sample Event Rain Total (Ft) | Sample Event Period Runoff Vol. (Gal) |
|---------|--------------------|----------------------------------|---|---|---------------------------------------|---------------------------------------|---|
| 126 | Impervious | 653,373 | 0.9 | 591,881 | 1.04 | 0.0867 | 383,723 |
| 120 | Pervious | 9,613 | 0.4 | 391,001 | 1.04 | 0.0667 | 303,723 |
| 115 1 | Impervious | 449,104 | 0.9 | 400 700 | 0 | 0 | 0 |
| 115.1 | Pervious | 13,938 | 0.4 | 409,792 | 0 | 0 | |
| 84.1 | Impervious | 23,958 | 0.9 | 21,562 | 1.25 | 0.1042 | 16,802 |
| 53 | Impervious | 209,720 | 0.9 | 100.400 | 4.4 | 0.4467 | 400,000 |
| 53 | Pervious | 4,280 | 0.4 | 190,460 | 1.4 | 0.1167 | 166,220 |
| 15 | Impervious | 2,009,431 | 0.8 | 0 444 224 | 1 40 | 0.4242 | 2 220 740 |
| 15 | Pervious | 2,009,431 | 0.4 | 2,411,321 | 1.49 | 0.1242 | 2,239,710 |
| PB01 | Impervious | 130,681 | 0.9 | 117,613 | 1.42 | 0.1183 | 104,110 |

10.0 Descriptive Statistics and Discussion of Event Station Monitoring Data

Descriptive statistics for the SW13 sampling period at each monitoring station are provided in Table 8, below. These statistics include minimum, maximum, average and median at static 1-hour interval periods for vault level, conductivity, salinity, transducer water temperature, and tidal stage. The method by which the rainfall statistics are calculated is on a "rolling 1-hour data window' in an attempt to provide a more accurate and representative assessment of the actual rainfall

conditions. Sampling period rainfall totals are also included as part of each station's rainfall information.

Table 8. Sampling Period Rainfall and Vault Parameter Descriptive Statistics

| Station ID | Statistics | Rainfall (1 hr) (in) | Vault Conductivity (uS/cm) | | ¹ Salinity (ppt) | trans temp (°C) | Tide Stage (ft) |
|------------|-------------|----------------------------|--------------------------------|-------|--------------------------------|-----------------------|--------------------|
| PSNS126 | Min | 0.00 | 0.15 | -17 | 2.00 | 4.13 | -1.19 |
| | Max | 0.16 | 3.98 | 3,093 | 2.89 | 8.27 | 10.80 |
| | Average | 0.07 | 1.14 | 208 | 2.01 | 5.98 | 5.37 |
| | Median | 0.06 | 0.38 | 90 | 2.00 | 5.93 | 6.41 |
| | Storm Total | 1.04 | | | | | |
| PSNS115.1 | Min | N/C | N/C | N/C | N/C | N/C | N/C |
| | Max | N/C | N/C | N/C | N/C | N/C | N/C |
| | Average | N/C | N/C | N/C | N/C | N/C | N/C |
| | Median | N/C | N/C | N/C | N/C | N/C | N/C |
| | Storm Total | N/C | | | | | |
| PSNS084.1 | Min | 0.00 | 0.14 | 152 | 2.00 | 4.99 | -1.19 |
| | Max | 0.21 | 7.46 | 2,175 | 2.02 | 9.92 | 10.80 |
| | Average | 0.10 | 3.33 | 300 | 2.00 | 6.83 | 5.47 |
| | Median | 0.09 | 3.44 | 220 | 2.00 | 6.75 | 7.28 |
| | Storm Total | 1.25 | | | | | |
| PSNS053 | Min | 0.00 | 0.01 | 104 | 2.00 | 4.42 | -1.19 |
| | Max | 0.23 | 5.92 | 372 | 2.00 | 23.45 | 11.27 |
| | Average | 0.09 | 3.18 | 130 | 2.00 | 7.49 | 5.69 |
| | Median | 0.08 | 3.78 | 119 | 2.00 | 7.19 | 6.88 |
| | Storm Total | 1.40 | | | | | |
| PSNS015 | Min | 0.00 | 0.42 | 54 | 2.00 | 4.17 | -1.19 |
| | Max | 0.24 | 8.44 | 1,619 | 2.00 | 10.24 | 10.80 |
| | Average | 0.09 | 3.67 | 217 | 2.00 | 6.26 | 5.42 |
| | Median | 0.08 | 3.17 | 128 | 2.00 | 6.17 | 6.24 |

| Station ID | Statistics | Rainfall (1 hr) (in) | Vault level (ft) | Conductivity (uS/cm) | ¹ Salinity (ppt) | trans temp (°C) | Tide Stage (ft) |
|------------|-------------|----------------------------|---------------------|-------------------------|--------------------------------|-----------------------|--------------------|
| | Storm Total | 1.49 | | | | | |
| PSNSPB01 | Min | 0.00 | 0.18 | -42 | 0.00 | 3.73 | -1.19 |
| | Max | 0.22 | 1.09 | 74 | 0.00 | 8.77 | 13.63 |
| | Average | 0.07 | 0.44 | 5 | 0.00 | 5.64 | 7.18 |
| | Median | 0.06 | 0.45 | 2 | 0.00 | 5.79 | 7.72 |
| | Storm Total | 1.42 | | | | | |

Table 8. Sampling Period Rainfall and Vault Parameter Descriptive Statistics

Hydrograph Assessment:

Hydrographs for each monitoring station (except PSNSPB01) showed typical PSNS basin rainfall responses. The Navy's rain gauge atop B427 reflected a similar rainfall signature as compared with the monitoring stations. Pipe level generally increased and decreased following the tidal fluctuation pattern - while rain water runoff kept the conductivity concentrations within the project designated freshwater range (≤2,000 µS/cm). This indicates freshwater storage or at least downstream movement of the expected salinity interface within the piping system. Temperatures generally decreased with the inflow of rainwater runoff and began to increase as the rain event tailed off and as pipe water levels decreased with outflow during the receding tidal stage. Backflow from rising tidal conditions, sans rainwater runoff, also caused temperatures to increase.

Since PSNSPB01 is not directly connected to Sinclair Inlet it does not receive tidewater, nor is it influenced (particularly regarding pressure effects) by tide level fluctuations. Water level for both the vault interior (filter chamber) and the sump (collection point for the under-drain system) are shown on the station hydrograph. Canister filter cycles are noted building to a certain level and then draining the vault level back down once their interior float mechanism is released from its seated position. A corresponding signature is noted in the sump hydrograph. Temperature is driven down during periods of runoff input and rises when the rainfall tails off. Conductivity is somewhat "choppy" on either side of the rain event. When enough runoff is available to submerge the conductivity probe a consistent reading is obtained - generally very low, less than $100 \,\mu\text{S/cm}$.

Of note is a curious conductivity spike at PSNS126 around mid-event. This may have been caused by some turbulent mixing within the pipe as it drained down to a point of less-than-full. Two long-duration temperature spikes were noted at PSNS053 around mid-event. This station experiences frequent inputs of warm water (perhaps from a steam condensate line). The receding

¹salinity calculations are based on an algorithm that has a lower range cut-off value of 2ppt. Actual field values may have been lower. N/C = values not calculated.

tide may have caused a rapid release from a buildup of this condensate into the vault, raising temperatures during two one-hour spikes.

Composite sample markers have been applied to the hydrographs to indicate total collection time (i.e. sample event period). Note that during this event no grab samples were collect and no samples of either type were collected at PSNS115.1. The monitoring station hydrographs, as well as the rainfall graph for B427, are attached.

11.0 Telemetry Data Summary Report: (TDSR)

A review of the telemetry data collected since the installation of the monitoring stations to a point just shortly after SW13 (11/15 to 12/17/12) was conducted. There were some minor anomalies in nearly all of the stations data sets due to initial installation and/or transducer maintenance tasks, as well as other issues described below.

Overall, data gaps and other anomalies during the actual SW13 storm event period were not noted, or were of non-significance. All sensors were in reasonable and accurate operation during the SW13 event. A TDSR report, comprised of a QA/QC data review and data set summary statistics, Tables 9 and 10 respectively, detailing issues associated with the collected vault and rainfall data and its general overall quality is included below.

Table 9. TDSR- QA/QC Data Review from 11/15 to 12/17/2012

| Site | Parameter | Issue | Start Date/Time | End Date/Time | G.A.R Level of Concern | Comments |
|------|-----------|--------------------------------|---------------------|---------------------|------------------------------|--|
| 84.1 | Level | Tidal and rainfall correlation | various | various | Amber | During periods of no rainfall, level within the vault does not match with corresponding tide stage. Indication of substantial base flow or other issues associated with drainpipe structure. |
| 84.1 | Temp | >20°C | various | various | Amber | 1486 anomalous high temperature readings throughout review period data set. Exact cause unknown. Field confirmation of these high temperatures has been noted. |
| 15 | Temp | >20°C | various | various | Amber | 9 anomalous high temperature readings throughout review period data set. Likely cause of these readings was maintenance activities. |
| 15 | All | Data Gap | 12/15/2012 10:00 | 12/15/2012 10:10 | Green | 10 minute data gap, unknown reason, likely maintenance / event prep related |
| PB01 | All | Data Gap | 12/12/2012 13:05 | 12/12/2012 15:15 | Green | 2.25 hr data gap (temp data exists from 1440), likely caused by transducer adjustment / re-positioning and calibration event |

Table 9. TDSR- QA/QC Data Review from 11/15 to 12/17/2012

| Site | Parameter | Issue | Start Date/Time | End Date/Time | G.A.R Level of Concern | Comments |
|-------|--------------|--------------------|---------------------|---------------------|------------------------------|--|
| PB01 | Conductivity | Negative values | various | various | Green | Although there were over 1700 occurrences of negative conductivity values, the concern is very low. The cause is due to the position of the cond. sensor being out of the water during most non-storm / non-runoff periods |
| PB01 | Vault Level | Negative values | 12/10/2012 14:15 | 12/10/2012 14:55 | Green | 40 minute period of negative vault transducer level, due to initial installation, corrected via calibration |
| 115.1 | All | Data Gap | various | various | Green | 4 data gaps were identified where all data was effected. Cause unknown. |
| 115.1 | Conductivity | Negative values | various | various | Amber | 226 negative conductivity readings, due to ultra-freshwater conditions mostly associated with storm event run-off |
| 115.1 | Conductivity | Missing data | 11/16/2012 10:15 | 11/19/2012 14:55 | Amber | 921 missing conductivity records during this period due to transducer / datalogger connection issues |
| 115.1 | Salinity | Null data | various | various | Amber | 26 null records where corresponding conductivity values should have generated a positive salinity calculation - cause unknown |
| 115.1 | Salinity | Missing data | 11/16/2012 10:15 | 11/19/2012 14:55 | Amber | 921 missing conductivity records during this period due to transducer / datalogger connection issues. |
| 115.1 | Salinity | Missing data | various | various | Amber | 226 additional missing salinity records due to corresponding negative conductivity values |
| 126 | All | Data Gap | various | various | Green | 4 data gaps were identified where all data was effected. Cause unknown. |
| 126 | Conductivity | Negative values | various | various | Amber | 594 negative conductivity readings, due to ultra-freshwater conditions mostly associated with storm event run-off |
| 126 | Salinity | Null data | various | various | Amber | 62 null records where corresponding conductivity values should have generated a positive salinity calculation - cause unknown |
| 126 | Salinity | Missing data | various | various | Amber | 594 missing salinity records due to corresponding negative conductivity values |

Table 10. TSDR - Data Set Summary Statistics from 11/15 to 12/17/2012

| Station | No. of Rcds | No. of Data Gaps | % Data Gap | Level Anomalies (# Rcds) | % Level Anomalies | Temp. Anomalies (# Rcds) | % Temp Anomalies | Cond. Anomalies (# Rcds) | % Cond Anomalies | Sal. Anomalies (# Rcds) | % Sal. Anomalies | Overall Data Set Completeness |
|-------------------|----------------|------------------------|------------------|--------------------------------|----------------------|--------------------------------|---------------------|--------------------------------|---------------------|-------------------------------|---------------------|-------------------------------------|
| 84.1 | 8064 | 0 | 0.0% | 101 | 125.0% | 1486 | 18.4% | 0 | 0.0% | 0 | 0.0% | 80.3% |
| 15 | 8928 | 1 | 0.0% | 0 | 0.0% | 9 | 0.1% | 0 | 0.0% | 0 | 0.0% | 99.9% |
| 53 | 8064 | 0 | 0.0% | 0 | 0.0% | 14 | 0.2% | 0 | 0.0% | 0 | 0.0% | 99.8% |
| ¹ PB01 | 1997 | 21 | 1.1% | 9 | 0.5% | 0 | 0.0% | 1784 | 89.3% | 0 | 0.0% | 9.2% |
| 115.1 | 8925 | 2072 | 23.2% | 0 | 0.0% | 0 | 0.0% | 226 | 2.5% | 26 | 0.3% | 74.0% |
| 126 | 9213 | 660 | 7.2% | 0 | 0.0% | 0 | 0.0% | 594 | 6.4% | 62 | 0.7% | 85.7% |

¹Conductivity anomalies (negative values) at PB01 are mainly due to transducer installation constraints, causing the conductivity sensor portion of the transducer assembly to be in open-air during most non-storm / no run-off periods, thus causing the sensor to indicate negative values. These negative conductivity readings do not adversely affect the quality of the overall data set.

12.0 Notable Field Anomalies and Variations to the 2012-13 PWPA

There were two notable field anomalies that occurred during SW13. These were; 1) no grab samples collected at any of the stations, and, 2) a composite sample was not generated at PSNS115.1.

- Grab samples were not collected from any of the monitoring stations at the direction of the Navy - mainly due to logistical considerations.
- A composite sample was not generated at PSNS115.1 during SW13 because discrete one-hour samples were not collected. Discrete samples were not collected due to a datalogger programming issue that existed, which was not observed during the testing phase. PSNS115.1 is the only station where the datalogger fully and completely controls the operation of the autosampler unit. In this mode additional "handshake" commands are required. One of these commands was missing, causing the autosampler not to response to pulses and other control and response queues causing the autosampler to sit idle during the event.

There were no anomalies either observed or otherwise noted after completion of the sampling event and review of the associated data that would have caused any of the SW13 samples to be non-representative of the conditions from which they were collected.

There were no deviations from or variations to methodologies described in the 2012-13 PWPA. As reported above, all project qualified samples were submitted to PNNL MSL within holding times and without incident. All support and sampling tasks, as well as collected samples, were managed as appropriate per the 2012-13 PWPA.

13.0 Action Items

Routine action items include resetting (reloading bottles, charging batteries, back flushing with DI water, etc.) all six monitoring stations for the next targetable / qualified storm sampling event and re-stocking of supplies. Routine station maintenance items (e.g. sensor cleaning and calibration, rain gauge maintenance, etc.) as well as storm set-up tasks will need to be completed as necessary and appropriate.

Non-routine action items include assessing and correcting the programming issue associated with the PSNS115.1 datalogger - autosampler communication protocol and maintenance of the Navy's rain gauge atop B427.

The current focus of the field efforts will be in maintaining proper station and equipment operational status, data and resource management and storm-tracking tasks.



Figure 1. Phase III Stormwater Monitoring Locations within the Puget Sound Naval Shipyard

Page Intentionally Left Blank

ATTACHMENTS

- Storm Event Summary and Sampling Information, Validation Checklist (Table A-1)
- Event Storm Controller Notes and Stormwater Field Sampling Forms
- Chain-of-Custody Forms
- Runoff Calculation Worksheet
- Station Hydrographs
- Autosampler Reports
- Weather Forecast Information

Table A-1. PSNS Non-Dry Dock Stormwater Monitoring Tasks Storm Event Summary and Sampling Information, Validation Checklist Stormwater Sampling Event #13 (12/16/12)



This form acknowledges representativeness criteria described in the project PWP.

Mark with "Yes" to acknowledge acceptable, "No" for not acceptable, "NA" or "--" if not applicable.

| Page 15 15 15 15 15 15 15 15 | Mark with "Yes" to acknowledge acceptable, "No" for not acceptable, "NA" or "" if not applicable. | | 1 | | | | |
|--|---|-----------------|----------------------|-----------------|-----------------|-----------------|------------------|
| Part | | • | | | | | |
| PRINS 1877 All Callages - Sample for North Country PRINS 1877 All Callages - Sample for Country PRINS 1877 All Ca | | | | | | | |
| As Financial Confirmation with without 20 may gar print or 18TE State (Date/Time) 1516/27 15170 5971579 | | | | | | | |
| Last Brand (P. 202)** related without 3-br age) Prior to STT Bland (Pland Time) 1970 15 10 | | | | | | | |
| Description for Particle (despite fiver) Composition (Depth Intro) (Particle (Depth Intro) Composition (Depth Intro) (Depth Intro) Composition (Depth Intro) (Depth Intro) Composition (Depth Intro) (Depth Intro) (Depth Intro) Composition (Depth Intro) (Dept | • | | | | | | |
| Rainfall Prior Sehres to Reain Event Start (rip) | | | | | | | |
| Rainfall Prior O-thus to Rain Exercise Start (a) 0.00 | | | | | | | |
| Start of Engine Protest Tested 12/96/27 4/15/16 | | | | | | | |
| Sampling Period Earth Date & Time 12/16/12/14/19 NA 12/16/12/14/19 12/16/12/14/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/19 12/16/12/14/14/19 12/16/12/14/14/14/14/14/14/14/14/14/14/14/14/14/ | | | | | | | |
| Sampling Period Call Date & Time | Start of Rainfall (Date/Time) | | | | | | |
| Sampling Period Duration (Incursion) | Sampling Period Start Date & Time | | NA | | | <u> </u> | · |
| Sampling Period Distributions 14.75 | Sampling Period End Date & Time | | | | | | |
| Sampling Period Total Rainfall (in) | Sampling Period Duration (hrs:mins) | | | | | | |
| Sampling Period Max 1-th Familial Intensity (Infinity) | Sampling Period Duration (hours) | | NA | 11.73 | 15.73 | 15.73 | 23.48 |
| Sampling Period Average 1-ft - Rainfall Interestity (in/hr) 0.07 N.M. 0.10 0.09 0.07 0.07 0.07 N.M. 16,812 106,220 22,317,10 141,1 | Sampling Period Total Rainfall (in) | | NA | 1.25 | 1.40 | 1.49 | 1.42 |
| Sumple Confloction Criteria: Sample Confloction Criteria: | Sampling Period Max 1-hr Rainfall Intensity (in/hr) | ļ | NA | 0.21 | | | |
| Sample Collection Citerias: N/A | | | NA | 0.10 | 0.09 | | |
| Signature Sign | Runoff volume calculated for sampling period (gallons) | 383,723 | NA | 16,802 | 166,220 | 2,239,710 | 104,110 |
| Seab Date Time NA NA NA NA NA NA NA N | ¹ Sample Collection Criteria: | | | | | | |
| Signature Sign | Grab sample ID | N/A | | N/A | N/A | N/A | N/A |
| Hydrograph stage at grab collection N/A N/ | Grab Date /Time | N/A | | N/A | N/A | N/A | N/A |
| Signature Sign | Grab sample conductivity value (μS/cm) | N/A | | N/A | N/A | N/A | N/A |
| Syrti3-0001 Syrti3-0001 Syrti3-0001 Syrti3-0001 Syrti3-0005 Syrti3-0004 Syrti3-0006 | Hydrograph stage at grab collection | N/A | | N/A | N/A | N/A | N/A |
| Composite Date Time | Grab parameters collected per PSNS PWP ? | N/A | | N/A | N/A | N/A | N/A |
| Deveral Composite conductivity value (mS/cm) 330 0 0 0 0 0 0 0 0 | Composite sample ID | SW13-0001 | | SW13-0002 | SW13-0006 | SW13-0005 | SW13-0004 |
| Secretal Composite underly value (NTU) 3 8 7 14 5 5 | Composite Date /Time | 12/17/2012 5:00 | | 12/17/2012 2:43 | 12/17/2012 6:20 | 12/17/2012 5:04 | 12/17/2012 10:18 |
| Composite volume (mt) | Overall Composite conductivity value (mS/cm) | 330 | during this event | 231 | 84 | 228 | 51 |
| Number of Bottles Collected During Sampling Event 22 Number of Bottles Included in Composite Sample 15 16 24 | Overall Composite turbidity value (NTU) | 3 | | 8 | 7 | 14 | 5 |
| Number of Bottles Included in Composite Sample 15 6 (24 24 24 24 24 24 24 24 | Composite volume (ml) | 6,000 | | 5,250 | 6,000 | 6,400 | 7,200 |
| Percentage of Total Sampling Period that Freshwater Conditions Occurred | Number of Bottles Collected During Sampling Event | 22 | | 11 (22hr span) | 20 | 21 | 24 |
| Ves | Number of Bottles Included in Composite Sample | 15 | | 6 (12hr span) | 15 | 16 | 24 |
| Carab sample duplicate ID | Percentage of Total Sampling Period that Freshwater Conditions Occurred | 68% | | 55% | 75% | 76% | 100% |
| State sample duplicate ID | Composite parameters collected per PSNS PWP ? | Yes | | Yes | Yes | Yes | Yes |
| Grab sample duplicate date and time N/A Grab sample duplicate conductivity value (µS/cm) N/A N/A Composite sample duplicate to ID N/A Composite sample duplicate date and time N/A Composite sample duplicate date and time N/A Composite sample duplicate date and time N/A Composite Duplicate conductivity value (µS/cm) N/A Coverall Composite Duplicate turbidity value (µS/cm) N/A Coverall Composite Duplicate turbidity value (µS/cm) N/A N/A Composite Duplicate turbidity value (µS/cm) N/A N/A Composite Duplicate turbidity value (µS/cm) N/A | ¹ QC Sample Summary Information: | | | | | | |
| Grab sample duplicate conductivity value (μS/cm) Composite sample duplicate ID N/A Composite sample duplicate ID N/A Overall Composite Duplicate date and time N/A Overall Composite Duplicate conductivity value (μS/cm) Overall Composite Duplicate conductivity value (μS/cm) N/A Overall Composite Duplicate value (μS/cm) N/A N/A N/A N/A N/A N/A N/A N/ | Grab sample duplicate ID | N/A | | N/A | N/A | N/A | N/A |
| Grab sample duplicate conductivity value (μS/cm) Composite sample duplicate ID N/A Composite sample duplicate ID N/A Overall Composite Duplicate date and time N/A Overall Composite Duplicate conductivity value (μS/cm) Overall Composite Duplicate conductivity value (μS/cm) N/A Overall Composite Duplicate value (μS/cm) N/A N/A N/A N/A N/A N/A N/A N/ | Grab sample duplicate date and time | N/A | | N/A | N/A | N/A | N/A |
| Composite sample duplicate ID Composite sample duplicate date and time Overall Composite Duplicate conductivity value (µS/cm) Overall Composite Duplicate conductivity value (µS/cm) N/A Overall Composite Duplicate volume (mI) N/A Overall Composite Duplicate volume (mI) N/A Overall Composite Duplicate volume (mI) N/A Swoot1 Swoot1 Swoot2 Swoot3 Swoot3 Swoot5 Swoot7 Swoot6 **Storm and Sample Validation:** Did event antecedent qualify per PSNS PWPA? (if no, then see next line) Was runoff occurring OR was the hydrograph at least 10% above background pipe level during grab collection? If no, explain in summary narrative. Were all 1-hr sampler bottles used for the Composite sample ≤2000 µS/cm? Vescomp | Grab sample duplicate conductivity value (µS/cm) | N/A | | N/A | N/A | N/A | N/A |
| Overall Composite Duplicate conductivity value (µS/cm) Overall Composite Duplicate turbidity value (NTU) N/A Overall Composite Duplicate turbidity value (NTU) N/A N/A Overall Composite Duplicate volume (ml) Associated Equipment Blank SW0011 SW0012 SW0013 SW0015 SW0017 SW0016 SW0017 SW0016 SW0017 SW0017 SW0018 SW0017 SW0018 SW0019 SW00 | | | No samples collected | SW13-0003 | N/A | | |
| Overall Composite Duplicate turbidity value (NTU) N/A Composite Duplicate volume (ml) Associated Equipment Blank Sw0011 Sw0012 Sw0013 Sw0015 Sw0015 Sw0016 Sw0016 Sw0016 Sw0016 Sw0017 Sw0016 Sw0017 Sw0016 Sw0017 Sw0016 Sw0017 Sw0016 Sw0018 Sw0017 Sw0016 Sw0018 Sw0017 Sw0018 Sw0017 Sw0016 Sw0018 Sw0017 Sw0018 Sw0017 Sw0016 Sw0018 Sw0017 Sw0018 Sw0018 Sw0017 Sw0018 Sw0017 Sw0016 Sw0018 Sw0017 Sw0018 Sw0018 Sw0017 Sw0018 Sw0018 Sw0017 Sw0018 Sw0018 Sw0018 Sw0017 Sw0018 | Composite sample duplicate date and time | N/A | during this event | 12/17/2012 2:43 | N/A | N/A | N/A |
| Composite Duplicate volume (ml) Associated Equipment Blank SW0011 SW0012 SW0013 SW0015 SW0017 SW0016 SW0017 SW0016 SW0016 SW0017 SW0016 NA Yes Yes Yes Yes Yes Yes Yes Ye | Overall Composite Duplicate conductivity value (µS/cm) | N/A | | 315 | N/A | N/A | N/A |
| Associated Equipment Blank Sw0011 Sw0012 Sw0013 Sw0015 Sw0017 Sw0016 | Overall Composite Duplicate turbidity value (NTU) | N/A | | 8 | N/A | N/A | N/A |
| 1 Storm and Sample Validation: Did event antecedent qualifity per PSNS PWPA? (if no, then see next line) Yes NA Yes Yes Yes Yes NO What was the total antecedent period amount overage, as % of rain event? NA NA NA NA NA NA NA NA NA N | Composite Duplicate volume (ml) | N/A | | 5,250 | N/A | N/A | N/A |
| Did event antecedent qualifiy per PSNS PWPA? (if no, then see next line) Yes NA Yes Yes Yes NO What was the total antecedent period amount overage, as % of rain event? NA NA NA NA NA NA NA NA NA N | Associated Equipment Blank | SW0011 | SW0012 | SW0013 | SW0015 | SW0017 | SW0016 |
| What was the total antecedent period amount overage, as % of rain event? NA NA NA NA NA NA NA NA NA N | ¹ Storm and Sample Validation: | | | | | | |
| What was the total antecedent period amount overage, as % of rain event? NA NA NA NA NA NA NA NA NA N | Did event antecedent qualifiv per PSNS PWPA? (if no. then see next line) | Yes | NA | Yes | Yes | Yes | No |
| Was runoff occurring OR was the hydrograph at least 10% above background pipe level during grab collection ? If no, explain in summary narrative. Were a minimum of 8 aliquots collected OR does the composite sample represent at least 75% of the stations storm event rain volume ? Were all 1-hr sampler bottles used for the Composite sample ≤2000 μS/cm ? Were all 1-hr sampler bottles used for the Composite sample ≤2000 μS/cm ? No N | | | | | | | |
| rain volume? Were all 1-hr sampler bottles used for the Composite sample ≤2000 μS/cm? Yes NA Yes | Was runoff occurring OR was the hydrograph at least 10% above background pipe level during grab collection ? If no, | | | | | | |
| Did any anomalous conditions exist that could make samples non-representative? Explain if "Yes" No | · · · · · · | Yes | NA | Yes | Yes | Yes | Yes |
| Did any anomalous conditions exist that could make samples non-representative? Explain if "Yes" No | Were all 1-hr sampler bottles used for the Composite sample ≤2000 μS/cm ? | Yes | NA | Yes | Yes | Yes | Yes |
| TO THE PAGE COMPANY OF THE | | | | No | | | No |
| | | Yes-comp | NA | Yes-comp | Yes-comp | Yes-comp | Yes-comp |

¹ If the answer to any of these questions is "No" OR indicate non-representative conditions, then these items should be explained in the Event Narrative.

| Date: | | 12/15/20 |)12 (2342) | _ | Sampling S | | | D. Metallo, | • | | | |
|----------------------------|--------------------|--------------------------------|---------------------------------|--------------------|---------------------------------|---|-----------------------------------|---------------------------------|--|-----------------|---------------|----------------|
| STE# | 13 | Antecedent Met ? | t Dry Cond. | Conditional | | | 0:33 PST -2.67 3:39 PST 6.14 | | | | | |
| Storm Controller: | | D. Metallo | | | Grab samp | ling Info. | Navy has su | uspended gr | ab sampling for this even | t | | |
| Pre-Storm / Weather | Details: | the day and r around 1.75". | night in the ea . The NAM sh | rly morning hou | rs, finally tam from 1000 to | pering off in that book about 2000, the | ne mid-mornin hen lighter rair | g hours, with n until around | tomorrow. The GFS has rai passing bands and periods midnight Sunday, tampering | of no rain unti | il 1400 Monda | y, with totals |
| Telemetry Measurements: | | | | | | DAT | E/TIME (24) | HR) | | | | |
| STATION: | 12/15/12 (2342) | 12/16/12 (0900) | 12/16/12 (1205) | 12/16/12 (1410) | 12/16/12 (1510) | 12/16/12 (1808) | 12/17/12 (0005) | 12/17/12 (0905) | 12/17/12 (1000-1130) | | | |
| PSNS015 Rain ¹ | .53/0.0 | .31/0.0 | .24/.01 | .17/.07 | | .59/.10 | 1.30/.09 | 1.56/0.0 | | | | |
| PSNS015 Level | 0.19 | 8.92 | 3.74 | 2.74 | | 7.89 | 0.78 | 10.66 | | | | |
| PSNS015 Cond. | 1605 | 42,900 | 32147 | 222 | | 84 | 153 | 40,450 | | | | |
| Smpl Marker | 4 | 4 | 4 | 8 | | 24 | 47 | 83 | | | | |
| PSNS084.1 Rain | 0.37/0.0 | .35/0.0 | .22/.01 | .16/.06 | .20/.06 | 54/.08 | 1.20/.07 | 1.46/0.0 | | | | |
| PSNS084.1 Level | 0.04 | 8.06 | 2.86 | 1.89 | 2.88 | 7.03 | 0.24 | 9.85 | | | | |
| PSNS084.1 Cond. | 2202 | 46,500 | 36,500 | 5,140 | 789 | 214 | 537 | 46,000 | | | | |
| Smpl Marker | 3 | 3 | 3 | 3 | 4 | 16 | 40 | 76 | | | | |
| PSNS115.1 Rain | .30/0.0 | .29/0.0 | .18/0.0 | .12/.06 | | .50/.08 | 1.13/.06 | 1.31/0.0 | | | | |
| PSNS115.1 Level | 0.05 | 11.96 | 6.76 | 5.89 | | 10.85 | 0.96 | 13.68 | | | | |
| PSNS115.1 Cond. | 4733 | 47100 | 10,500 | 1,848 | | 4 | 269 | 47,100 | | | | |
| Smpl Marker | 2 | 2 | 2 | 3 | | 16 | 40 | 76 | Sampler Prgms manally ended, shut off | | | |
| PSNS053 Rain | .42/0.0 | .39/0.0 | .24/.01 | no | .24/.07 | .61/.11 | 1.30/.07 | 1.57/0.0 | samplers, storm over | | | |
| PSNS053 Level | 0.01 | 3 | 0.01 | connection | 0.77 | 4.61 | 3.13 | 4.02 | | | | |
| PSNS053 Cond. | 98 | 46,200 | 889 | | 145 | 128 | 120 | 43,600 | | | | |
| Smpl Marker | 7 | 7 | 7 | | 10 | 22 | 45 | 81 | | | | |
| PSNS126 Rain | .29/0.0 | .28/0/0 | .17/.01 | .14/.06 | | .44/.06 | .96/.05 | 1.14/0.0 | | | | |
| PSNS126 Level | 0.13 | 4.8 | 0.16 | 0.3 | | 3.63 | 0.33 | 6.46 | | | | |
| PSNS126 Cond. | 2018 | 45600 | 5308 | 226 | | 8 | 36 | 45,750 | | | | |
| Smpl Marker | 0 | 0 | 0 | 1 | | 16 | 40 | 76 | | | | |
| PSNS PB01 Rain | .53/0.0 | .51/0.0 | .19/.02 | .16/.06 | | .50/.06 | no | 1.42/0.0 | | | | |
| PSNS PB01 Level | 0.18 | 0.18 | 0.29 | 0.47 | | 0.54 | connection | 0.2 | | | | |
| PSNS PB01 Cond. | na | na | na | 22 | | 8 | | na | | | | |
| Smpl Marker | 7 | 7 | 13 | 21 | | 36 | | 97 | | | | |
| Rain dephs are repor | ted as 1-hr/2 | 24-hr totals | | | yellow highl | ight indicate | s station acti | vely samplin | g | | | |

PSNS NDDSW Monitoring Project Storm Control Work Sheet, Continued

Sht Rev. 121412

Sheet 2 of <u>2</u>

| Date: | | 12/1 | 5/2012 | | Sampling S | Support Pers | sonnel: | D.Metallo, E | 3. Rupert | | | | |
|-----------------------------|----------|-----------|-----------|------------|------------|--------------|-------------|--------------|-----------|--------------------------------------|-----------------------------|-----------|--|
| STE# | 13 | Storm Con | troller: | D. Metallo | | Strm Evnt | Start / Stp | | | , , | PB01; Stop 1 & PB01, end | | |
| Enabling Information | n: | | | | | | | | | | | | |
| Sample Staion: | PSN | S015 | PSN | S084.1 | PSNS | S115.1 | PSN | S 053 | PSN | S126 | PSNS | PB01 | |
| Rain enable (in/hr) | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | 0.05 | |
| Level Enable (ft) | 20 | 0.3 | 20 | 0.3 | 20 | 0.3 | 20 | 0.3 | 20 | 0.3 | 20 | 0.24 | |
| Cond. (µS/cm) | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | NA | NA | |
| Repeat. Cond Set ? | no | no | no | no | yes | yes | no | no | no | no | yes-level | yes-level | |
| Pacing Rate (min) | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | |
| Sampler Batt Vdc | 12.66 | 12.63 | 12.69 | 12.43 | 12.52 | 12.51 | 12.59 | 12.59 | 12.74 | 12.74 | 12.62 | 12.61 | |
| Pre-event Smpl Mrk Value | 4 | 4 | 3 | 3 | 2 | 2 | 7 | 7 | 3 | 0 | 7 | 7 | |
| Date | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 15-Dec | 16-Dec | |
| Time | 1630 | 2342 | 1630 | 2347 | 1630 | 2355 | 1630 | 2351 | 1630 | 2356 | 1630 | 1216 | |
| Comp Du | p?/where | : | PSNS084.1 | | | | Gral | Dup ? / wh | ere: | None (no grabs collected this event) | | | |

EVENT NOTES:

- 1. Logger Batt @ 115.1 = 11.88 vdc 12/15 (1621) need to swap out
- 2. PB01 station is being triggered via rain and sump level only. The repeatable function is set on for sump level
- 3. Called Bob Johnston to discuss current storm situation and targeting/triggering particulars. Will continue to monitor rainfall and approaching fronts. Will arm all stations with "live" triggering conditions later this evening (~2200 to 2300).
- 4. PB01 enabled @ 1049 12/16/12



PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

ver.020411

| Station: /2/ | MH/CB#: KTIO | Loc. Descrip. P 10 410 | 0 |
|--------------|--------------|------------------------|--------------|
| 166 | 010 | Duilo 760 | Page: 1 of L |

| | Section 1. Statio | n Reset and Inspection | payris yor scarori | | |
|--|-------------------|------------------------------------|--------------------|--|--|
| Personnel: | Weather: | Arrival Date | e/Time: | | |
| Carry-over maintenance to do prior to set- | up: | | done? | | |
| Sampler Battery Voltage | | Changed? Y N | New voltage | | |
| Modem Battery Voltage | | Changed? Y N | New voltage | | |
| Sample Tubing & Strainer OK? | | Sampler Info. | | | |
| Transducer & Telem | etry System Info. | Time Display OK? (Yes/No) | | | |
| Trands. Cable OK? | | Internal Sampler Tubing OK? | | | |
| Trands. Desiccant OK (Yes/No) | | Tubing Replaced? (Yes/No) | | | |
| Telem. Box Desiccant OK (Yes/No) | ~ | Normal Smpler Program or Dup. | .? | | |
| Modem Status | N.W. | Bottles Loaded ? | | | |
| Notes (including channel condition): | | Lid Status? | | | |
| | | Backflushed with DI? | | | |
| | | Suction line & quick connect atta | ached? | | |
| | | Smplr Status (on/off) / last scree | n | | |

| | Section 2. Storm Setu | p and Inspection | |
|---|------------------------|------------------------------------|-----------------|
| Personnel: B. Rupert | Weather: Overcust, ten | Arrival Date/Time | : 1415 12/14/12 |
| Sampler Battery Voltage | 12.76 | Changed? Y N | New voltage — |
| Modem Battery Voltage | 11.97 | Changed? (Y) N | New voltage |
| Sample Tubing & Strainer OK? | OIL | Sampler Se | tup |
| Transducer & Multi-me | eter Setup | Time/Date Display OK? (Yes/No) | Ves |
| Transducer Cable OK? | 016 | Aliquot Vol. Cal.'ed (Y/N & vol.) | VESPZ40ML |
| Multi-meter Cable OK | OL | Program Reviewed (Yes/No), Dup ? | VES / Normal |
| Recorded Level (FT) | 2,42 | Lids off bottles? | 4 25 |
| Measured Level (FT) | 2,38 | Diagnostics/Distrubutor arm check? | YES |
| Offset Diff (FT) | 012 = -0.18/ NEW 0.21 | Backflush with DI? | 100 |
| Level Adjusted ? | Yes -lowl goal | Storm Reset (1, enter) Completed | VES |
| Cond. Sonde Type (YSI6820 of INW-CT2X) | 1 1 1 1 1 | Last screen PrG Dis | 1455 FR 14-De |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas. Val. = Diff. = | (>10% adj. offset); Offset = Net | w Rec Val = |
| Notes: (e.g. enabling values, cond cal. meter make/mo | | (>10% adj. offset); Offset = Ne | w Rec Val = |

| | Section 3. Gra | b Sample Collection |
|--|------------------------------------|---|
| Personnel: | Weather: | Arrival Date/Time: |
| On Composite (Bottle #/ Aliq #) | | Conductivity Reading (µS/cm): |
| Grab Parameters Collected | | Salinity Reading (PPT): |
| Grab Sample ID | | Temp. Reading (°C): |
| Grab Date/Time | | Turbidity Reading (NTU) |
| Grab Dup ID | | Equipment running correctly? |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?): |
| Sample Observations (notify storm controller if sa | ample turbidity, odor, color, foam | , or sheen look out of the ordinary): which?: |
| Storm Contoller notified (Y or N/A)?: | | Grab MS/MSD Collected ? Y / N Ice OK? |
| Notes: (what meter was used for site readings, etc.) | No grabs | collected during this event |
| | | |



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: 126 | continued from previous page | | Page: 2 of 2 |
|--|----------------------------------|---------------------------------|--------------------------------|
| Section | on 4. Post-Storm Sample Colle | ection (for grab, comp or both) | |
| Personnel: BR, IS | Weather: Mostly Swan | y breezy 30°5 Arrival [| Date/Time: 12/17/17 1115 |
| Sampler Battery Voltage | Good | Changed? Y N | New voltage — |
| Telemtery Battery Voltage | Good | Changed? Y (N) | New voltage |
| Additional Grabs (IDs, date/time) | NA | | |
| Additional Dup Grab (IDs, date/time) | NA 1416 | | |
| Composite Begin Time (date/time) | 12-16-12 (1320) | Sampler Report Downloaded | ? Yes |
| Last Aliquot Taken (date/time, bott #, aliq #) | 12-17-12 (1004) | BTL 21 4/4 (11 | |
| Total Composite Sample Volume Collected | 21 6+15 | | |
| Aliquots missed/NLD (date/time/bott #/aliq #) | 6/4 6 3/// | 3/4, 142/4 all = 1 | |
| Channel Condition / Observations (oil/sheen, | floatables, turbidity, suspended | solids, discoloration, odor)? | OK . |
| Storm Contoller notified (Y or N/A)?: NA | Which parameter?: | NA | |
| Notes: Manually paused 1 | 4/17/12 (1004) BT | L 214/4 | |
| Maintenance Needed: Re-SetS | | | |
| | Section 5. Compositing Sch | eme and QC Sampling | |
| Personnel: DM. BR TS | | Date/Time: 12-17-12 (| (230) |
| Conductivity & Turbidity Meter/s Info.(Manuf. | Turb = Scient | | |
| Conductivity & Turbidity Testing (List ind. sm | 1 1 1 1 | 1. 1 | 110 / 1 |
| 1717 131 Y 1 | 400/6/4 | 3 225/1/ Y | 19 43480/1/ N |
| 2 30/8/4 8 | 120/5/ Y 1 | 4 344/11 4 | 20 43320/11 N |
| 3 240/9/4 9 | 415/2/ Y 15 | 5 570/11 Y | 21 42210/1/N |
| 4 260/5/4 10 | 163/3/4 11 | 23360/1/N | 72 NE 37001/1/1 |
| 5 57/5/ Y 11 | 142/2/ 4 1 | 7 42580/11 N | 23 NC |
| 6 65/8/Y 12 | 74 121 4 10 | | 24 NC |
| Brief Description of Compositing Scheme: (in | clude what bottles, based on be | ench-top screening above, where | used for the overall composite |
| sample) BTL 15 had ~ 400 | ml and was used | d as the "volume" | control BTL measure |
| Used BTLS 1-15 | @ 400-ml ed | | |
| Overall Composite Info. (include conductivity Cond = 330 Turb | | | valysis = per PWPA |
| Composite Sample ID & Time: | | 500) | |
| Field Blank Collected? (date/time) | Previously | | |
| Blank ID: | NA | | |
| Duplicate comp sample? Yes/No | NO | | |
| | 100 | | |

NC= Not collected



PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: //= / | MH/CB#: b 1101 6 | Loc. Descrip. DOZO | 2 |
|----------------|------------------|--------------------|--------------|
| 1/3 1/ | 0 4860 | Mear 5819 | Page: 1 of 4 |

| | Section 1. Stati | on Reset and Inspection | pageopio gionor |
|--|-------------------|-------------------------------------|-----------------|
| Personnel: | Weather: | Arrival Date/ | Time: |
| Carry-over maintenance to do prior to set- | up: | | done? |
| Sampler Battery Voltage | | Changed? Y N | New voltage |
| Modem Battery Voltage | | Changed? Y N | New voltage |
| Sample Tubing & Strainer OK? | | Sampl | er Info. |
| Transducer & Teleme | etry System Info. | Time Display OK? (Yes/No) | |
| Trands. Cable OK? | | Internal Sampler Tubing OK? | |
| Trands. Desiccant OK (Yes/No) | | Tubing Replaced? (Yes/No) | |
| Telem. Box Desiccant OK (Yes/No) | | Normal Smpler Program or Dup. | ? |
| Modem Status | | Bottles Loaded ? | |
| Notes (including channel condition): | | Lid Status? | |
| | | Backflushed with DI? | \ |
| | | Suction line & quick connect attac | hed? |
| | | Smplr Status (on/off) / last screen | |

| | Section 2. Storm Se | tup and Inspection | |
|--|----------------------|------------------------------------|----------------|
| Personnel: B. Rusert | Weather: ove-cast - | temp 50's Arrival Date/Time: | 12/14/12 2/5/5 |
| Sampler Battery Voltage | 12.51 | Changed? Y (N) | New voltage |
| Modem Battery Voltage | 12.03 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | OIL | Sampler Sets | ıp |
| Transducer & Multi-me | eter Setup | Time/Date Display OK? (Yes/No) | oll |
| Transducer Cable OK? | oil | Aliquot Vol. Cal.'ed (Y/N & vol.) | VES & ZYOML |
| Multi-meter Cable OK | OK | Program Reviewed (Yes/No), Dup ? | Yes-Nu-mil |
| Recorded Level (FT) | 10.80 | Lids off bottles? | 405 |
| Measured Level (FT) | 10.93 | Diagnostics/Distrubutor arm check? | 405 |
| Offset Diff (FT) old without = 014 | @ MW 0,00 | Backflush with DI? | NU |
| Level Adjusted ? | Vas-geed | Storm Reset (1, enter) Completed | Yes |
| Cond. Sonde Type (YSI6820 or INW-CT2X) | NIA | Last screen Pros Dis 1400 | FR 12-14 |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas. Val. = Diff. = | (>10% adj. offset); Offset = New | Rec Val = |

| | Section 3. G | rab Sample Collection | |
|--|-----------------------------------|---|---------|
| Personnel: | Weather: | me: | |
| On Composite (Bottle #/ Aliq #) | | Conductivity Reading (µS/cm): | |
| Grab Parameters Collected | | Salinity Reading (PPT): | |
| Grab Sample ID | 11 | Temp. Reading (°C): | |
| Grab Date/Time | | Turbidity Reading (NTU) | |
| Grab Dup ID | | Equipment running correctly? | |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?): | |
| Sample Observations (notify storm controller if | sample turbidity, odor, color, fo | am, or sheen look out of the ordinary): which?: | |
| Storm Contoller notified (Y or N/A)?: | | Grab MS/MSD Collected ? Y / N | Ice OK? |
| Notes: (what meter was used for site readings, etc.) | No grab Sami | oles collected during this even | + |



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: PSNS 115 | continued from previous pa | ge | Page: 4 of 2 |
|---|--|---|--|
| Sec | tion 4. Post-Storm Sample | Collection (for grab, comp or both) | |
| Personnel: BR, IS | Weather: Sunny 30 | S. Windy Arrival Date/Ti | me: 12-17-12 (1100) |
| Sampler Battery Voltage | God | Changed? Y N | New voltage |
| Felemtery Battery Voltage | Good | Changed? Y N | New voltage |
| Additional Grabs (IDs, date/time) | No | | |
| Additional Dup Grab (IDs, date/time) | No | | A AVAILABLE TO THE STATE OF THE |
| Composite Begin Time (date/time) | 0 | Sampler Report Downloaded ? | Yes |
| ast Aliquot Taken (date/time, bott #, aliq | #) | | |
| Total Composite Sample Volume Collected | | ollected | 10 |
| Aliquots missed/NLD (date/time/bott #/aliq Channel Condition / Observations (oil/shee | | nded solids, discoloration, odor)? | bled to a literal class |
| STATE OF TAKEN | .,,,, | | |
| Storm Contoller notified (Y or N/A)?: NA | Which parameter?: | NA | |
| Notes: 1) Sander did not f. | wition as design | ed, no water collected a | Juvini event |
| Total O Sampor Air par Fr | cocio- us accign | est, its total collection is | 9 |
| Maintenance Needed: Assess Fund | tionality glitch a | conduct typical reset for | - wext sample event |
| | Section 5. Compositing | Scheme and QC Sampling | |
| Personnel: | | Date/Time: | |
| Conductivity & Turbidity Meter/s Info.(Man | | | - IVAN |
| Conductivity & Turbidity Testing (List ind. s | smplr bottle; cond. reading in | µS/cm; turb. reading in NTŲ; will ind. smpl b | e included in comp smpl Y/N): |
| | | | |
| | | | - |
| | | | |
| | | | |
| | | | |
| 3*1 | | | |
| | | | |
| Brief Description of Compositing Scheme: sample) No Comp Some | | on bench-top screening above, where used | for the overall composite |
| Overall Composite Info. (include conductiv | ity and turbidity measuremen | ts, volume and requested analysis) | |
| Composite Sample ID & Time: | | | |
| Field Blank Collected? (date/time) | | | |
| Blank ID: | | | |
| Duplicate comp sample? Yes/No | | | |
| Duplicate sample ID | A COLUMN TO THE PARTY OF THE PA | | |
| NOTES: | | | |



PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

ver 02041

| Station: O(1) | MH/CB#: | Loc. Descrip. | 2 |
|---------------|---------|---|--------------|
| 6911 | 551 | 1 | Page: 1 of 4 |

| | Section 1. Station Re | set and Inspection | |
|---|-----------------------|---------------------------------------|-------------|
| Personnel: | Weather: | Arrival Date/Tim | e: |
| Carry-over maintenance to do prior to set | -up: | | done? |
| Sampler Battery Voltage | | Changed? Y N | New voltage |
| Modem Battery Voltage | | Changed? Y N | New voltage |
| Sample Tubing & Strainer OK? | | Sampler II | nfo. |
| Transducer & Telemetry System Info. | | Time Display OK? (Yes/No) | |
| Trands. Cable OK? | 70 | Internal Sampler Tubing OK? | |
| Trands. Desiccant OK (Yes/No) | | Tubing Replaced? (Yes/No) | |
| Telem. Box Desiccant OK (Yes/No) | | Normal Smpler Program or Dup. ? | |
| Modem Status | | Bottles Loaded ? | |
| Notes (including channel condition): | | Lid Status? | |
| | | Backflushed with DI? | |
| | | Suction line & quick connect attached | 1? |
| | | Smplr Status (on/off) / last screen | |

| | Section 2. Storm Setu | ip and Inspection | |
|--|------------------------|------------------------------------|----------------|
| Personnel: B. Rupert | Weather: overcust - Ni | Sht Time Arrival Date/Time: | 12-14-12 01630 |
| Sampler Battery Voltage | 12.58 | Changed? Y N | New voltage — |
| Modem Battery Voltage | 12.72 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | OIC | Sampler Set | up |
| Transducer & Multi-meter Setup | | Time/Date Display OK? (Yes/No) | OIL |
| Transducer Cable OK? | OIL | Aliquot Vol. Cal.'ed (Y/N & vol.) | You & Izome |
| Multi-meter Cable OK | OIC | Program Reviewed (Yes/No), Dup ? | Yes - Dup |
| Recorded Level (FT) | 2127 HH | Lids off bottles? | YES |
| Measured Level (FT) | 7.92 | Diagnostics/Distrubutor arm check? | XES |
| Offset Diff (FT) Old offset = 2.58 | New 0.21 | Backflush with DI? | |
| Level Adjusted ? | Mewlevel = 7.82(good) | Storm Reset (1, enter) Completed | 405 |
| Cond. Sonde Type (YSI6820 or INW-CT2X) | | Last screen Proj Dis 1656 | FR 14-20 |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas. Val. = Diff. = | | Rec Val = |

| | Section 3. G | rab Sample Collection | |
|---|------------------------------------|---|------------|
| Personnel: | Weather: | Arrival Date/Ti | me: |
| On Composite (Bottle #/ Aliq #) | 931 | Conductivity Reading (µS/cm): | |
| Grab Parameters Collected | | Salinity Reading (PPT): | |
| Grab Sample ID | | Temp. Reading (°C): | |
| Grab Date/Time | | Turbidity Reading (NTU) | |
| Grab Dup ID | | Equipment running correctly? | |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?): | |
| Sample Observations (notify storm controller if | sample turbidity, odor, color, for | am, or sheen look out of the ordinary): which?: | |
| Storm Contoller notified (Y or N/A)?; | | Grab MS/MSD Collected ? Y / N | Ice OK? |
| Notes: (what meter was used for site readings, etc. | No grab S | camples collected during | this event |



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: | PSNS 084.1 | continued from previous page | | Page: 2 of 2 |
|------------------------|---|---|---------------------------------|------------------------------------|
| | Secti | on 4. Post-Storm Sample Collect | ion (for grab, comp or both |) |
| Personnel: | BR, IS | Weather: Mostly Sunny, 1 | over24, 30°5 Arrival | Date/Time: 12-17-12 (1130) |
| Sampler Bat | | Good | Changed? Y (N) | New voltage |
| Telemtery Ba | attery Voltage | Good | Changed? Y (N) | New voltage |
| Additional Gr | abs (IDs, date/time) | NO | | |
| Additional Du | ıp Grab (IDs, date/time) | NO | | And the second |
| Composite B | egin Time (date/time) | 12-16-12 (1459) | Sampler Report Downloade | 1? Yes |
| ast Aliquot | Taken (date/time, bott #, aliq #) | | 2 3/3 (1128) | at Emphasics |
| otal Compo | site Sample Volume Collected | | | |
| Aliquots miss | sed/NLD (date/time/bott #/aliq # | | | Total Your Public |
| Channel Con | dition / Observations (oil/sheer | n, floatables, turbidity, suspended so | olids, discoloration, odor)? | OK-typical |
| | ller notified (Y or N/A)?: NA | Which parameter?: | NA | |
| Notes: Lo | cation set up | for duplicate co | lection | |
| Maintenance | Needed: Re-set st | intion for next sam | ding event | |
| 0.5 | | | | |
| | | Section 5. Compositing Schen | | |
| ersonnel: | DM, BR, IS & Turbidity Meter/s Info.(Manus | Ward America | Date/Time: 12-17-12 | (1320) |
| Conductivity | L= YSI EC300 & Turbidity Testing (List ind. sr | Turb = Scientificant bottle; cond. reading in \mu S/cm; | turb. reading in NTU; will ind. | smpl be included in comp smpl Y/N) |
| 2 321 | | 195/11/Y 13 203/8/Y (14) | $\frac{1620/2/N}{1600/2/N}$ | (20) 42 390/1/N |
| 3.86 | 112/Y 9 | 241/17/4 5 | . 41570/1/N | 21, 42500/1/N |
| 4) 78 | 1101 y (10) | 238/9/ Y (16 |) 42300/1/ N | (22)42700/11N |
| 5.46 | 18 14 11. | 124/5/ V 17 | 42900/1/N | 23. Empty |
| 1 47 | 17/1/ | 110 131 V (19 | 11/00/11 N | 211 5 |
| Prief Descrin | tion of Compositing Scheme: | include what bottles, based on bend | / / / | e used for the overall composite |
| ample) | DD BTI'S - AK | ormal Sample: Use | A BTL'S 1,3,5,7,9 | 11 ~ 875 ml from ea. |
| | BTL's = dupli | | | |
| Overall Com | posite Info. (include conductivit | y and turbidity measurements, volu | me and requested analysis) | vol = 5750 . 1 |
| Vorma | 1: Cond = 231 us/ | MBNTU VOL = 525 | 50 ml Dup: con | d=315.45/cm 8 NTW |
| | | W13-0002 (024 | 4 | |
| | Collected? (date/time) | | | |
| Blank ID: | one stout (autoratio) | previously | | |
| | mp sample? Yes/No | VES VES | | |
| Company of the Company | | | 0242) | |
| Duplicate sar | inple to | SW13-00031 | 0243) | |

NOTES:



PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

ver 0204

| Station: | MH/CB#: 27110 | Loc. Descrip. NE Corner RILLS | 7 |
|----------|---------------|-------------------------------|--------------|
| 055 | 2149 | NE Corner 13449 | Page: 1 of 6 |

| | Section 1. Station Res | et and Inspection | |
|--|------------------------|-----------------------------------|-----------------------------|
| Personnel: | Weather: | Arrival Da | ate/Time: [2-14-12-(17-36)] |
| Carry-over maintenance to do prior to set- | up: | | done? |
| Sampler Battery Voltage | | Changed? Y N | New voltage |
| Modem Battery Voltage | | Changed? Y N | New voltage |
| Sample Tubing & Strainer OK? | | Sampler Info. | |
| Transducer & Telemetry System Info. | | Time Display OK? (Yes/No) | 3. |
| Trands. Cable OK? | Rn | Internal Sampler Tubing OK? | |
| Trands. Desiccant OK (Yes/No) | | Tubing Replaced? (Yes/No) | |
| Telem. Box Desiccant OK (Yes/No) | | Normal Smpler Program or Du | p. ? |
| Modem Status | | Bottles Loaded ? | |
| Notes (including channel condition): | | Lid Status? | |
| | | Backflushed with DI? | |
| | | Suction line & quick connect at | ttached? |
| | | Smplr Status (on/off) / last scre | een |

| | Section 2. Storm Se | rtup and inspection | |
|--|-----------------------|------------------------------------|---------------|
| Personnel: B. Ruset | Weather: oce-cust - 1 | Irsh + Time Arrival Date/Time | 12-14-12-1731 |
| Sampler Battery Voltage | 12.64 | Changed? Y (N) | New voltage |
| Modem Battery Voltage | 12.43 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | O(Z Sampler Setu | | tup |
| Transducer & Multi-meter Setup | | Time/Date Display OK? (Yes/No) | OIL |
| Transducer Cable OK? | OK | Aliquot Vol. Cal.'ed (Y/N & vol.) | ollezyone |
| Multi-meter Cable OK | OL | Program Reviewed (Yes/No), Dup? | Ves- no-mal |
| Recorded Level (FT) | 2.02 | Lids off bottles? | Y25 |
| Measured Level (FT) | 2.16 | Diagnostics/Distrubutor arm check? | VES |
| Offset Diff (FT) 012 offset=0,25 | New= 0,17 | Backflush with DI? | |
| Level Adjusted ? | New crel = 2.01 (902 | Storm Reset (1, enter) Completed | 125 |
| Cond. Sonde Type (YSI6820 or INW-CT2X) | 1 | Last screen Prox Dis 1754 | FR 14-Dec |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas, Val. = Diff. = | (>10% adj. offset); Offset = Net | w Rec Val = |

| The second second | Section 3. G | rab Sample Collection | | |
|--|---------------------------------------|---|----|--|
| Personnel: | Weather: | Weather: Arrival Date/Time: | | |
| On Composite (Bottle #/ Aliq #) | | Conductivity Reading (µS/cm): | | |
| Grab Parameters Collected | | Salinity Reading (PPT): | | |
| Grab Sample ID | | Temp. Reading (°C): | | |
| Grab Date/Time | | Turbidity Reading (NTU) | | |
| Grab Dup ID | | Equipment running correctly? | | |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?): | | |
| Sample Observations (notify storm controller | if sample turbidity, odor, color, for | am, or sheen look out of the ordinary): which?: | | |
| Storm Contoller notified (Y or N/A)?: | | Grab MS/MSD Collected ? Y' / N Ice OK? | | |
| Notes: (what meter was used for site readings, etc | No grab 30 | imples collected during this ever | nt | |



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: PSNS 053 | continued from previous pa | je | Page: 4 of 4 |
|---|--|--|---|
| Sec | tion 4. Post-Storm Sample | Collection (for grab, comp or both) | |
| Personnel: RR T5 | | fly sunary windy Arrival Da | ate/Time: /2-17-12 (1015) |
| Sampler Battery Voltage | Good | Changed? Y (N) | New voltage |
| Telemtery Battery Voltage | Good | Changed? Y (N) | New voltage |
| Additional Grabs (IDs, date/time) | NO. | | |
| Additional Dup Grab (IDs, date/time) | No | | 2 |
| Composite Begin Time (date/time) | 12-16-12 (143 | () Sampler Report Downloaded | Yes |
| _ast Aliquot Taken (date/time, bott #, aliq # | | | 1/65 |
| Total Composite Sample Volume Collected | 1 70 BTIS 14 | mpty & 2 partials | |
| Aliquots missed/NLD (date/time/bott #/aliq BTLs 21-24 empty dud | #) from 14 2/4 - | > 16 214 - massed - | |
| Channel Condition / Observations (oil/shee | en, floatables, turbidity, susper | nded solids, discoloration, odor)? |)K |
| Storm Contoller notified (Y or N/A)?: | A Which parameter?: | NA | |
| Notes: Manually paused | 1stopped (1020 |) 12-17 BTL 20 @ | 3/3 |
| Maintenance Needed: Typical r | esets | | |
| | Section 5. Compositing | Scheme and QC Sampling | |
| Personnel: BR DM TS | | Date/Time: 12-17-12 | 115115) |
| Conductivity & Turbidity Testing (List ind. s 1 264 / 5 / Y 7. 2 35 / 9 / Y 8. 3 20 / 9 / Y 9. | mplr bottle; cond. reading in p 12 / 6 / Y 12 / 13 / Y 19 / 7 / Y | S/cm; turb. reading in NTU; will ind. si 13. 15/8/Y 14. 60/15/Y 15. empty | 19. 28380/2/N 20, 28550/2/N 21, Empty |
| 4 13/4/ Y 10 | . 16/5/ Y | 16.139/9/Y | 22. |
| G 7 / G / Y 12 Brief Description of Compositing Scheme: | . 10/3/ Y | 18. 2756013/N | 24° V |
| sample) Used BTLs 1-14 | +16, 400-ml | from ea = ~6,00 | 20 m 1 |
| BTL'S 17 - ZD too b Overall Composite Info. (include conductiv | nigh cond. to quity and turbidity measurement | ralify, BTLS 15 & 21. | -24 empty |
| Cond = 84 us/cm, - | | Vol. = 6000-m1 A | ralysis per PWPA |
| Composite Sample ID & Time: | SW13-0006 | (0620) | |
| Field Blank Collected? (date/time) | previously | | |
| Blank ID: | NA ' | | |
| Duplicate comp sample? Yes/No | NO | | |
| Duplicate sample ID | 440 | | |

NOTES:



PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

ver.020411

Loc. Descrip. MCD's Station: PSNS 015 MH/CB#: A42 Page: 1 of 2

| | | | pages per station |
|---|--|--|-------------------|
| | Section 1. Station Res | et and Inspection | |
| Personnel: DM, BR | Weather: Rainwing . 3 | 30°5 Arrival Date/Time | 1005 12-15-12 |
| Carry-over maintenance to do prior to set | | A Paragraphic Control | done? |
| Sampler Battery Voltage | 12.61 | Changed? Y N | New voltage — |
| Modem Battery Voltage | 12.38 | Changed? Y N | New voltage - |
| Sample Tubing & Strainer OK? | Ves | Sampler Info. | |
| Transducer & Telemetry System Info. | | Time Display OK? (Yes/No) | Vied to correct |
| Trands. Cable OK? | Yes | Internal Sampler Tubing OK? | Y |
| Trands. Desiccant OK (Yes/No) | Yes | Tubing Replaced? (Yes/No) | N |
| Telem. Box Desiccant OK (Yes/No) | Yes | Normal Smpler Program or Dup. ? | Nor. |
| Modem Status | Operational | Bottles Loaded ? | Y |
| Notes (including channel condition): - Re- prymied I.sco, in: tial for PhaseIII | | Lid Status? | OFF |
| | | Backflushed with DI? | У |
| | 1, | Suction line & quick connect attached? | Ý |
| | | Smplr Status (on/off) / last screen | Prim Dis. 1034 |

| | Section 2. Storm S | Setup and Inspection | |
|--|----------------------|------------------------------------|-----------------|
| Personnel: DM, BR | Weather: | Arrival Date/Time | : 12-15-12 1005 |
| Sampler Battery Voltage | 12.61 | Changed? Y (N) | New voltage |
| Modem Battery Voltage | 12.38 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | Y Sampler Setup | | tup |
| Transducer & Multi-meter Setup | | Time/Date Display OK? (Yes/No) | ok |
| Transducer Cable OK? | У | Aliquot Vol. Cal.'ed (Y/N & vol.) | Y |
| Multi-meter Cable OK | NA | Program Reviewed (Yes/No), Dup ? | Y-Normal |
| Recorded Level (FT) | 5.34 | Lids off bottles? | V |
| Measured Level (FT) | 5.34 | Diagnostics/Distrubutor arm check? | V |
| Offset Diff (FT) | 2.00 0.17' | Backflush with DI? | Ý |
| Level Adjusted ? | N | Storm Reset (1, enter) Completed | ý |
| Cond. Sonde Type (YSI6820 or INW-CT2X) | CTZX | Last screen | Parm DIS. 1036 |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas. Val. = Diff. = | (>10% adj. offset); Offset = Ne | w Rec Val = |

| | Section 3. G | rab Sample Collection | | |
|--|--------------------------------------|---|-------|--|
| Personnel: | Weather: | Weather: Arrival Date/Time: | | |
| On Composite (Bottle #/ Aliq #) | | Conductivity Reading (µS/cm): | | |
| Grab Parameters Collected | | Salinity Reading (PPT): | | |
| Grab Sample ID | | Temp. Reading (°C): | | |
| Grab Date/Time | | Turbidity Reading (NTU) | | |
| Grab Dup ID | | Equipment running correctly? | | |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?): | | |
| Sample Observations (notify storm controller | if sample turbidity, odor, color, fo | am, or sheen look out of the ordinary): which?: | | |
| Storm Contoller notified (Y or N/A)?: | | Grab MS/MSD Collected ? Y / N Ic | e OK? | |
| Notes: (what meter was used for site readings, etc | No grab sam, | ples collected during this ev | rent | |



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

Page: 2 of 2 Station: PSNS 015 continued from previous page Section 4. Post-Storm Sample Collection (for grab, comp or both) Weather: Mostly sunny, 30°s, winds Arrival Date/Time: 12-17-12 Personnel: BR 1000 Good Sampler Battery Voltage Changed? W New voltage (N New voltage Good Telemtery Battery Voltage Changed? NA Additional Grabs (IDs, date/time) Additional Dup Grab (IDs, date/time) Sampler Report Downloaded ? Yes 12-16-12 (1320) Composite Begin Time (date/time) 12-17-12 (1004) BT1 21 4/4 Last Aliquot Taken (date/time, bott #, aliq #) Total Composite Sample Volume Collected 100% all bottles Aliquots missed/NLD (date/time/bott #/aliq #) BTL 13 243 of 4, BTL 14 2of 4, BTL 11 3 of 4 Channel Condition / Observations (oil/sheen, floatables, turbidity, suspended solids, discoloration, odor...)? Storm Contoller notified (Y or N/A)?: Which parameter?: Manually stopped sampler at end of BTL 21 Re-sets Maintenance Needed:

| | Section 5. Compositing Scheme and QC Sampling |
|--|---|
| Personnel: DM BR IS | Date/Time: 12-17-12 (1510) |
| Conductivity & Turbidity Meter/s Info.(Manuf. | ., Model, Serial#, Cal.info.) |
| Cond = EC 300 YSI | Turb = Scientific Inc. MicroTip TPI; both Navy IN: |
| Conductivity & Turbidity Testing (List ind. sm | pplr bottle; cond. reading in μS/cm; turb. reading in NTU; will ind. smpl be included in comp smpl Y/N): |
| 1. 574/14/ Y 7. | 17 / 20 / Y 13. 45/6/ Y 19. 29860/1/N |
| 2.380/16/ Y 8. | 37/11/4 14. 79/3/ 4 20.30/20/1/N |
| 3.137 21 / 4 9. | 63/ 17/ 4 15. 215/6/4 21. 30420/11 N |
| 4. 33 / 35/ Y 10. | 100/11/4/16. 725/4/4 22. Empty |
| 5. 30 (28/ Y II. | 76/6/ Y 17. 27720/2/ XN 23. |
| 6. 20/16/4 12. | 71 / 5/ Y 18. 28340/2/XN 24. V |
| | nclude what bottles, based on bench-top screening above, where used for the overall composite le for Comp Sample, 400-MI from each BTL, |
| 17-21 did not qualify, | BTLS 22-24 were empty due to manual stop |
| Overall Composite Info. (include conductivity | y and turbidity measurements, volume and requested analysis) |
| Cond = 228 us/cm Ti | urb = 14 NTU Vol = 6400-MI Analysis per PWPA |
| Composite Sample ID & Time: | SW13-0005 (0504) |
| Field Blank Collected? (date/time) | previously |
| Blank ID: | I'NA / |
| Duplicate comp sample? Yes/No | NO |
| Duplicate sample ID | WA |
| NOTES: | |



Notes: (what meter was used for site readings, etc.)

PSNS NPDES Non-Dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

ver 02041

| Station: PSNS PB01 | MH/CB#: SDMH -OID | Loc. Descrip. Per B Quay | Wall Page: 1 of 2 |
|--|--|---------------------------------------|--------------------|
| | Section 1. Station Rese | et and Inspection | pages per station |
| Personnel: DM, BR | Weather: Rain/Slee | 1 2 2 | e: /2-15-12 (1130) |
| Carry-over maintenance to do prior to set- | 11-11/100 | | done? |
| Sampler Battery Voltage | 12.20 | Changed? Y N | New voltage |
| Modem Battery Voltage | 12.60 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | Yes | Sampler Ir | |
| Transducer & Telem | 140 | Time Display OK? (Yes/No) | n/ |
| Trands, Cable OK? | V | Internal Sampler Tubing OK? | V |
| Trands. Desiccant OK (Yes/No) | (| Tubing Replaced? (Yes/No) | 1/1/ |
| Telem. Box Desiccant OK (Yes/No) | 1 | Normal Smpler Program or Dup. ? | Normal. |
| Modern Status | Constant | Bottles Loaded ? | V |
| Notes (including channel condition): | Operational | Lid Status? | 6FF |
| ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | | Backflushed with DI? | V |
| | | Suction line & quick connect attached | 2 1 |
| | | Smplr Status (on/off) / last screen | & Pram Dis |
| | | ompir otatas (orivon) r last screen. | 10 tram UIS |
| | Section 2. Storm Se | tup and Inspection | |
| Personnel: DM / BR | | Leet, 34° Arrival Date/Tim | e: 17-15 |
| Sampler Battery Voltage | 12.29 | Changed? Y (N) | New voltage |
| Modem Battery Voltage | 12.60 | Changed? Y (N) | New voltage |
| Sample Tubing & Strainer OK? | 12.00 | Sampler Se | |
| Transducer & Muli | ti-meter Setup | Time/Date Display OK? (Yes/No) | Ves |
| Transducer Cable OK? | V | Aliquot Vol. Cal.'ed (Y/N & vol.) | Yes |
| Multi-meter Cable OK | NA | Program Reviewed (Yes/No), Dup? | Yes - Normal |
| Recorded Level (FT) | 0.45 (vault) 0:43 | Lids off bottles? | Off-Ves |
| Measured Level (FT) | 0.48 6.43 | P Diagnostics/Distrubutor arm check? | V |
| Offset Diff (FT) | 0.03 / 0.00 | Backflush with DI? | 1/ |
| Level Adjusted ? | Ves for Vault | Storm Reset (1, enter) Completed | V |
| Cond. Sonde Type (YSI6820 or INW-CT2 | | Last screen Pram Di | 1256 |
| Cond. Sonde Cal. Info. : Recorded Val. = | Meas. Val. = Diff. = | | ew Rec Val = |
| Notes: (e.g. enabling values, cond cal. meter make | se/model/ser#, etc.) Cal. ied M | nd-WV | 6-1-9- |
| | Section 3. Grab Sam | ple Collection | |
| Personnel: | Weather: | Arrival Date/ | Time: |
| On Composite (Bottle #/ Aliq #) | | Conductivity Reading (µS/cm): | |
| Grab Parameters Collected | | Salinity Reading (PPT): | |
| Grab Sample ID | | Temp. Reading (°C): | |
| Grab Date/Time | | Turbidity Reading (NTU) | |
| Grab Dup ID | | Equipment running correctly? | |
| Grab Dup Date/Time | | Sampler Battery Voltage (Changed?) | |
| Sample Observations (notify storm controller i | if sample turbidity, odor, color, foam, or she | | * |
| Storm Contoller notified (Y or N/A)? | | Grab MS/MSD Collected 2 Y / N | Ice OK2 |

No grab samples collected during this event,



PSNS NPDES Non-dry Dock Monitoring and Support

Telemetry, 24-1L bottle set-up

Taylor Associates, Inc.

| Station: PSNS PBOI | continued from previous pag | • | Page: 2 of 2 |
|--|---|--|--|
| Section | on 4. Post-Storm Sample C | collection (for grab, comp or both) | |
| Personnel: BR IS | Weather: Mostly Sun | | te/Time: 12-17-12 (1030) |
| Sampler Battery Voltage | Good | Changed? Y N | New voltage |
| elemtery Battery Voltage | Good | Changed? Y (N) | New voltage |
| dditional Grabs (IDs, date/time) | No | IF STORY AND STORY | |
| dditional Dup Grab (IDs, date/time) | NA | | |
| omposite Begin Time (date/time) | 12-16-12 (104 | Sampler Report Downloaded ? | Yes |
| ast Aliquot Taken (date/time, bott #, aliq #) | 12-17-12 BTL | 24 3/3 (1018) | |
| otal Composite Sample Volume Collected | 100% 23 BTL | 4 BTLIS 75% (30f | 4 aliquots) |
| Aliquots missed/NLD (date/time/bott #/aliq #) | NONE | 24 | The management |
| Channel Condition / Observations (oil/sheen | floatables, turbidity, suspen | ded solids, discoloration, odor)? | pical/vault OK |
| storm Contoller notified (Y or N/A)?: NA | Which parameter?: | MA | |
| lotes: | | | |
| | | | |
| laintenance Needed: Typical Re- | set for next sto | rm event | |
| | | | |
| | Section 5. Compositing S | Scheme and QC Sampling | |
| ersonnel: DM, BR, IS | | Date/Time: 12-17-12 (/ | 420) |
| Conductivity & Turbidity Meter/s Info.(Manuf. | 이 가지 않는 얼마나 아이를 되어 가지 않는데 아니라 아이를 하는데 하다면 하다면 했다. | 15-11 | 1 |
| conductivity & Turbidity Testing (List ind. sm | | Company of the property of the second | All the state of t |
| 051111 | 38/10/ Y | 12 28/3/ V | 19. 43/1/4 |
| 0.11110 | 11141 V | 13. 30/3/ | |
| | 91151 | 14. 48/2/ 4 | 20. 45/11 Y |
| | 34/5/ Y | 15. 42/41, Y | 21. 45/11 4 |
| 1. 16/12/ 4 10. | 31/4/ 4 | 16. 37/3/ Y | 27. 49/11 Y |
| 5. 61/10/ Y 11. | 37/5/ Y | 17. 39/2/ 4 | 23. 5/1/ 4 |
| 2. 50/14/ Y 12. | 33/4/ Y | 18. 41/11/4 | 24 5/11 V |
| rief Description of Compositing Scheme: (in | clude what bottles, based or | bench-top screening above, where u | sed for the overall composite |
| ample) Used ~ 300ml from | | | |
| Chacott C - 1 | 7.50 - 1.00 | | |
| | | in the second second | |
| Cond. = 51 us/cm Tuy | | | isis per PWPA |
| | 3W13-000L | 1 (1018) | quita de la companya del companya de la companya del companya de la companya de l |
| ield Blank Collected? (date/time) | Dreviously Co | Mocted | |
| lank ID: | NA | The Property of the Parket of | |
| Ouplicate comp sample? Yes/No | 1/0 | | |

Duplicate sample ID NOTES:

EQUIPMENT BLANK SAMPLES, PRE SW-13

| | | | | , | | | <u> </u> | | | | | Λ | | | | | | | | | |
|-------------------|---|--|----------------------|-----------------------------------|--|---------------|------------|---|------------------------------|-------------------------|---------------------|-----|-------------------------|-----------|------|----------------------|--|---|------------------------------|-----------------------|---|
| | SAMPLE CHAIN Date: Page: / Project No.: Project: | of CUSTODY FO of / N4523A10MP000 PSNSNon-dry Do | _ 934 Amend.2 | | ı | EB o An | are hem | an ical Sep | dy's q s q * pf ara | ed (20) | only cerv 12) | to | ex nr) *(5 QAI | ; 12 | ÿP . | | 1529 We Laborato | ciences Lab st Sequim E ry: Battelle Jill Brand Phone: (3 | Bay Road MSL Jenberger | | |
| 1742 173 1717 175 | SW/3-EX Sample Label SWOOII SWOOIZ SWOOIX SWOOIX SWOOIK SWOOIK | Station ID PSNS 126 PSNS 11S.1 PSNS 84.1 PTOGRAD EQUY PSNS US 3 PSNS US 3 PSNS US M | Collection Date/Time | Matrix W W W U U U U U U | XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX | Z 100 | X X DOC | A X X X X X X X X X X X X X X X X X X X | X X K TME/BIME 2002 | X Y TPH | Turbidity • | | | | | トートトー No. containers | Sample Type (Grab vs. Comp) | 3174* -Storm# | Cond. (Turl Re | μS/c b. (N adir | Comp. cm) and ITU) ngs F Sla-ks |
| | Relinquished by: | 130 11-n | | 1520 | | Re | | ved | | | | | To | 112 | . 15 | 36 | Total # o | f Containe | rs: | | |
| | Relinquished by: | Signature Printed Name Signature | Date Company Date | Time | | | Su | | Sig /Cu Prii by: | inatui Lal nted l | √∠ (Nam | bel | • | | | | Sample I Distributi 1) PNN 2) CAS | ind duliposition: | NW S | | |
| | | Printed Name | Company | | | | | | Pri | nted | Nam | e | | | | | 3) TAI | <u>,</u> | | | |

| Date: 12/17/2 | RM | SW-13 STORMWATER SAMPLES | | | | | | | | S | Marine Sciences Laboratory | | | | | | | | | | |
|--|---|--|----------------|------------------|-----------------------|-----------------------|---------------------------------------|--------|--|----------------|----------------------------|---|----------------|------------|------------------------------|------------------|-----|---|----------------------------|--|-----|
| Page: 1 Project No.: Project: | Analyze parameters per QAP/FSP | | | | | | | | 1529 West Sequim Bay Road Laboratory: Battelle MSL Attention: Jill Brandenberger Phone: (360) 681-4564 | | | | | | | | | | | | |
| Sample Label SW13 - 0001 SW13 - 0002 SW13 - 0004 SW13 - 0005 SW13 - 0006 | Station ID PS.NS 126 PS.NS 084.1 DUP 084.1 PS.NS PB01 PS.NS 015 PS.NS 053 | 12-17-12 (0243 12-17-12 (0243 12-17-12 (1018 12-17-12 (0504 | | X X X X | X X X X X | X X X X X | × × × × × × × × × × × × × × × × × × × | XXXXXX | ТРН | Turbidity(2) | | | No. containers | Co | mple ype Frab vs. omp) | Stor | 231 | Cond. Tur Ri 330 335 51 228 84 | (µS/ b. (l eadi / | Complement of the complement o | and |
| | Signature | Date Cardno-TEC Company | (1640) Time | | | | <u> </u> | Prin | | e M Name | ku | 0 | 84= | Shi Sar | pmen mple C | f Cont t Meth | od: | s: 6 | | | |
| Relinquished by: | Signature | Date | Time | | | ceiv | | | natur | e | | | | 1) 2) | tribution PNNL CAS TAI | | | | | | |
| (C) (C) | Printed Name | Company | | | | | | Prin | ted 1 | Name | <u>e</u> | | | <u>L_</u> | | | | | | | |

1) Storm water samples

2) Turbidity measured @ Stormwater lab w/ Scientific Inc. Microtip TPI

PSNS NDDSW Monitoring Stormwater Sampling Event SW13 (12/16/2013) Stormwater Outfall Total Discharge Volume Estimation Equations


| PSNS Drainage Basin | Total Basin Area (ft²) | Type of Surface | Percentage | Area of Basin Surface Type (ft²) | ¹ Runoff Coefficient | Area of Basin Surface Type with Maximum Coefficient Value Applied (ft²) | ² Total Discharge Volume (ft ³) | |
|------------------------|------------------------|-----------------|------------|-------------------------------------|------------------------------------|---|---|--|
| 126 | 662,986 | Impervious | 98.55 | 653,373 | 0.9 | 588,036 | R(591,881) | |
| 120 | 002,900 | Pervious | 1.45 | 9,613 | 0.4 | 3,845 | | |
| 115.1 | 463,042 | Impervious | 97 | 449,151 | 0.9 | 404,236 | R(409,792) | |
| 113.1 | | Pervious | 3 | 13,891 | 0.4 | 5,556 | 11(400,102) | |
| 84.1 | 23,958 | Impervious | 100 | 23,958 | 0.9 | 21,562 | R(21,562) | |
| 53 | 214,000 | Impervious | 98 | 209720 | 0.9 | 188,748 | P(100.460) | |
| 55 | | Pervious | 2 | 4,280 | 0.4 | 1,712 | R(190,460) | |
| 15 | 4,018,862 | Impervious | 50 | 2,009,431 | 0.8 | 1,607,549 | R(2,411,321) | |
| 15 | | Pervious | 50 | 2,009,431 | 0.4 | 803,772 | Γ(2,411,321) | |
| PB01 | 130,681 | Impervious | 100 | 130,681 | 0.9 | 117,613 | R(117,613) | |

Calculation Worksheet:


| STATION | Combined Drainage Area (FT ²) | ENTER: Smpl Evnt Rain Total (in) | Sampl Evnt Rain Total (FT) | STE Runoff Vol. (gal) |
|---------|--|-------------------------------------|-------------------------------|-----------------------|
| 126 | 591,881 | 1.04 | 0.0867 | 383,723 |
| 115 | 409,792 | 0.00 | 0.0000 | 0 |
| 84.1 | 21,562 | 1.25 | 0.1042 | 16,802 |
| 53 | 190,460 | 1.40 | 0.1167 | 166,220 |
| 15 | 2,411,321 | 1.49 | 0.1242 | 2,239,710 |
| PB01 | 117,613 | 1.42 | 0.1183 | 104,110 |


No Grab Samples Collected During Event


PSNS 126 SW13 12-16-2012































PSNS PB01 SW13 12-16-2012



Dec 2012

12/16/2012 10:20:00 AM - 12/17/2012 11:20:00 AM

B427 Rainfall SW13 12-16-2012



SW13 126 Smplr Rpt

| ********** PROGRAM SETTINGS ********* |
|--|
| PROGRAM NAME: "PSNS126 " SITE DESCRIPTION: "PSNS126 " |
| UNITS SELECTED: LENGTH: ft |
| 24, 1000 ml BTLS 19 ft SUCTION LINE 13 ft SUCTION HEAD 0 RINSES, 0 RETRIES |
| ONE-PART PROGRAM |
| PACING: FLOW, EVERY 1 PULSES SAMPLE AT START |
| DISTRIBUTION: 4 SAMPLES/BOTTLE |
| VOLUME: 240 ml SAMPLES |
| ENABLE: NONE PROGRAMMED |
| ENABLE: ONCE ENABLED, STAY ENABLED SAMPLE AT ENABLE |
| ENABLE: 0 PAUSE & RESUMES |
| NO DELAY TO START |
| LIQUID DETECT ON NO RAIN GAGE |

-----NO YSI SONDE MASTER/SLAVE OFF BTL FULL DETECT OFF TIMED BACKLIGHT -----**EVENT MARK SENT DURING PUMP CYCLE** PUMP COUNTS FOR **EACH PURGE CYCLE:** 200 PRE-SAMPLE **AUTO POST-SAMPLE** -----I/O1= NONE I/O2= NONE I/O3= NONE -----**0 ANALOG OUTPUTS** NO PERIODIC **SERIAL OUTPUT** -----NO DIALOUT CONDITIONS SET SAMPLER ID# 3293179321 11:29 17-DEC-12 Hardware: B2 Software: 3.26 ****** SAMPLING RESULTS ******* SITE: PSNS126 PROGRAM: PSNS126 Program Started at 15:56 FR 14-DEC-12 Nominal Sample Volume = 240 ml COUNT TO SAMPLE BOTTLE TIME SOURCE ERROR LIQUID -----15:56 PGM DISABLED ----- SU 16-DEC-12 -----14:16 PGM ENABLED

1,4 1 14:16 Ε 492 F 2,4 1 14:30 489 1 14:45 F 3,4 490 4.4 1 15:00 F 493 1,4 2 15:15 F 495 2,4 2 15:30 F 490

SW13 126 Smplr Rpt

| 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 4,4 4,4 4,4 4,4 4,4 4,4 4,4 4 | 2233334444555556666677778888899991010 | 15:45 16:00 16:15 16:30 16:45 17:00 17:15 17:30 17:45 18:00 18:15 18:30 18:45 19:00 19:15 19:30 19:45 20:00 20:15 20:30 20:45 21:00 21:15 22:30 22:15 22:30 23:15 23:30 23:45 | F F F F F F F F F F F F F F F F F F F | 493 489 491 486 487 478 481 473 471 473 471 467 470 471 473 481 483 483 483 490 496 499 495 501 501 501 501 501 501 497 |
|---|--|---|--|--|
| 4,4 1,4 2,4 3,4 4,4 1,4 2,4 3,4 4,4 1,4 2,4 3,4 | 10 11 11 11 12 12 12 12 13 13 | MO 17- 00:00 00:15 00:30 00:45 01:00 01:15 01:30 01:45 02:00 02:15 02:30 02:45 | DEC-1: F F F F F F F F F | 2 |

SW13 126 Smplr Rpt

```
13 03:00
                 F
                         503
4,4
                 F
1,4
     14 03:15
                        503
     14 03:30
2,4
                 F
                        569
3,4
     14 03:45
                 F NM
                 F NM
4,4
     14 04:00
1,4
     15 04:15
                 F NM
2,4
     15 04:30
                 F NM
3,4
     15 04:45
                 F NM
4,4
     15 05:00
                 F
                        497
                 F
     16
        05:15
                        490
1,4
2,4
     16 05:30
                 F
                        487
                 F
     16 05:45
3,4
                        480
4,4
     16
        06:00
                 F
                        476
                 F
1,4
     17
        06:15
                        475
2,4
     17
        06:30
                 F
                        466
                 F
3,4
     17
        06:45
                        463
                 F
4,4
     17
        07:00
                        460
     18 07:15
                 F
1,4
                        458
     18 07:30
                 F
2,4
                        463
                 F
3,4
     18 07:45
                        454
                 F
4,4
     18
        08:00
                        459
1,4
     19
        08:15
                 F
                        457
                 F
2,4
     19
        08:30
                        453
                 F
3,4
     19 08:45
                        459
4,4
     19
        09:00
                 F
                        461
                 F
1,4
     20 09:15
                        454
        09:30
                 F
2,4
     20
                        463
     20
                 F
3,4
        09:45
                        462
                 F
4,4
     20
        10:00
                        465
                 F
1,4
     21
         10:15
                        468
                 F
2,4
     21
         10:30
                        466
     21
        10:45
                 F
3,4
                        473
         11:00
                 F
4,4
     21
                        477
     22 11:15
                 F
1,1
                        477
       11:16 MANUAL PAUSE
      11:16 PGM STOPPED 17-DEC
SOURCE E ==> ENABLE
SOURCE F ==> FLOW
 ERROR NM ==> NO MORE LIQUID!
```

```
****** PROGRAM SETTINGS ********
 PROGRAM NAME:
 "PSNS084DUP"
SITE DESCRIPTION:
  "PSNS084DUP"
  -----
 UNITS SELECTED:
  LENGTH: ft
  5 MINUTE
 DATA INTERVAL
24, 1000 ml BTLS
16 ft SUCTION LINE
15 ft SUCTION HEAD
0 RINSES, 0 RETRIES
ONE-PART PROGRAM
  PACING:
 FLOW, EVERY
   1 PULSES
 SAMPLE AT START
  -----
 DISTRIBUTION:
2 BOTTLES/SAMPLE
 8 SAMPLES/BOTTLE
RUN CONTINUOUSLY
  VOLUME:
 120 ml SAMPLES
  -----
  ENABLE:
 NONE PROGRAMMED
  ENABLE:
 ONCE ENABLED.
 STAY ENABLED
 SAMPLE AT ENABLE
  ENABLE:
0 PAUSE & RESUMES
```

NO DELAY TO START

LIQUID DETECT ON 0.01 inch TIP **RAIN GAGE** -----NO YSI SONDE -----MASTER/SLAVE OFF BTL FULL DETECT OFF TIMED BACKLIGHT **EVENT MARK SENT DURING PUMP CYCLE** PUMP COUNTS FOR **EACH PURGE CYCLE:** 200 PRE-SAMPLE **AUTO POST-SAMPLE** -----I/O1= NONE I/O2= NONE I/O3= NONE **0 ANALOG OUTPUTS** NO PERIODIC SERIAL OUTPUT -----NO DIALOUT **CONDITIONS SET** SAMPLER ID# 3293179316 11:48 17-DEC-12 Hardware: B2 Software: 3.26 ****** SAMPLING RESULTS ******** SITE: PSNS084DUP PROGRAM: PSNS084DUP Program Started at 16:47 FR 14-DEC-12 Nominal Sample Volume = 120 ml COUNT TO SAMPLE BOTTLE TIME SOURCE ERROR LIQUID 16:47 PGM DISABLED ------ SU 16-DEC-12 ------14:59 PGM ENABLED

SW13 84.1 Smplr Rpt

| 1,8,8,8,8,8,8,8,8,8,8,8,8,8,8,8,8,8,8,8 | 1-2 14:59 1-2 15:13 1-2 15:28 1-2 15:43 1-2 15:58 1-2 16:13 1-2 16:28 1-2 16:43 3-4 16:58 3-4 17:13 3-4 17:28 3-4 17:43 3-4 17:58 3-4 17:58 3-4 18:13 3-4 18:28 3-4 18:43 5-6 19:13 5-6 19:28 5-6 19:43 5-6 19:58 5-6 20:13 5-6 20:28 5-6 20:43 7-8 20:58 7-8 21:13 7-8 21:28 7-8 21:43 7-8 21:28 7-8 22:28 7-8 22:28 7-8 22:43 9-10 23:28 9-10 23:28 9-10 23:58 | 8 F F F F F F F F F F F F F F F F F F F | 504 497 497 495 496 494 490 489 488 484 482 484 482 484 482 483 487 496 502 508 510 516 522 535 536 532 531 532 532 |
|--|--|---|---|
| 6,8 7,8 8,8 1,8 2,8 3,8 4,8 5,8 | 9-10 25:30 9-10 00:13 9-10 00:28 9-10 00:43 11-12 00:58 11-12 01:13 11-12 01:28 11-12 01:43 11-12 01:58 | | |
| 0,0 | 11 12 01.00 | ' | 002 |

SW13 84.1 Smplr Rpt

```
532
6,8 11-12 02:13
                  F
7,8 11-12 02:28
                  F
                          532
                  F
8,8 11-12 02:43
                          532
                   F
1,8 13-14 02:58
                          534
                   F
2,8 13-14 03:13
                          536
3,8 13-14 03:28
                   F
                          534
4,8 13-14 03:43
                   F
                          534
                   F
5,8 13-14 03:58
                          528
6,8 13-14 04:13
                   F
                          525
                   F
7,8 13-14 04:28
                          520
8,8 13-14 04:43
                   F
                          516
                   F
1,8 15-16 04:58
                          503
2,8 15-16 05:13
                   F
                          501
3,8 15-16 05:28
                   F
                          498
4,8 15-16 05:43
                   F
                          492
                   F
5,8 15-16 05:58
                          485
6,8 15-16 06:13
                   F
                          484
                   F
7,8 15-16 06:28
                          480
8,8 15-16 06:43
                   F
                          474
1,8 17-18 06:58
                   F
                          473
2,8 17-18 07:13
                   F
                          472
3,8 17-18 07:28
                   F
                          470
4,8 17-18 07:43
                   F
                          470
                   F
5,8 17-18 07:58
                          468
                   F
6.8 17-18 08:13
                          468
7,8 17-18 08:28
                   F
                          468
                   F
8,8 17-18 08:43
                          468
1,8 19-20 08:58
                   F
                          469
2,8 19-20 09:13
                   F
                          470
3,8 19-20 09:28
                   F
                          472
                   F
4,8 19-20 09:43
                          473
                   F
5,8 19-20 09:58
                          475
                   F
6,8 19-20 10:13
                          480
                   F
7,8 19-20 10:28
                          478
8,8 19-20 10:43
                   F
                          481
1,3 21-22 10:58
                   F
                          482
2,3 21-22 11:13
                  F
                          488
3,3 21-22 11:28
                          490
       11:40 MANUAL PAUSE
       11:41 PGM STOPPED 17-DEC
SOURCE E ==> ENABLE
SOURCE F ==> FLOW
```

SW13 053 Smplr Rpt

| *********** PROGRAM SETTINGS ********** |
|---|
| PROGRAM NAME: "PSNS 053 " SITE DESCRIPTION: "PSNS 053 " |
| UNITS SELECTED: LENGTH: ft |
| 24, 1000 ml BTLS 19 ft SUCTION LINE 11 ft SUCTION HEAD 0 RINSES, 0 RETRIES |
| ONE-PART PROGRAM |
| PACING: FLOW, EVERY 1 PULSES SAMPLE AT START |
| DISTRIBUTION: 4 SAMPLES/BOTTLE |
| VOLUME: 240 ml SAMPLES |
| ENABLE: NONE PROGRAMMED |
| ENABLE: ONCE ENABLED, STAY ENABLED SAMPLE AT ENABLE |
| ENABLE: 0 PAUSE & RESUMES |
| NO DELAY TO START |
| |
| LIQUID DETECT ON NO RAIN GAGE |

-----NO YSI SONDE MASTER/SLAVE OFF BTL FULL DETECT OFF TIMED BACKLIGHT -----**EVENT MARK SENT DURING PUMP CYCLE** PUMP COUNTS FOR **EACH PURGE CYCLE:** 200 PRE-SAMPLE **AUTO POST-SAMPLE** -----I/O1= NONE I/O2= NONE I/O3= NONE -----**0 ANALOG OUTPUTS** NO PERIODIC **SERIAL OUTPUT** -----NO DIALOUT CONDITIONS SET SAMPLER ID# 3293179322 10:50 17-DEC-12 Hardware: B2 Software: 3.26 ****** SAMPLING RESULTS ******* SITE: PSNS 053 PROGRAM: PSNS 053 Program Started at 17:53 FR 14-DEC-12 Nominal Sample Volume = 240 ml COUNT TO SAMPLE BOTTLE TIME SOURCE ERROR LIQUID -----17:54 PGM DISABLED ----- SU 16-DEC-12 -----14:36 PGM ENABLED 1,4 1 14:36 Ε 479 F 2,4 1 14:50 476 F 3,4 1 15:05 475

476

468

470

4.4

1,4

2,4

1 15:20

2 15:35

2 15:50

F

F

F

SW13 053 Smplr Rpt

| 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 3,4 4,4 1,4 2,4 4,4 1,4 2,4 4,4 1,4 1,4 1,4 1,4 1,4 1,4 1,4 1,4 1 | 223333444455555666667777888889999100 | 16:05 16:20 16:35 16:50 17:05 17:20 17:35 17:50 18:05 18:05 18:20 19:05 19:05 19:05 20:05 20:20 20:35 20:20 20:35 21:20 21:35 21:50 22:05 22:20 22:35 22:50 23:35 23:50 | F F F F F F F F F F F F F F F F F F F | 464 456 455 457 458 462 461 458 461 455 450 455 451 458 451 458 451 457 458 459 457 463 463 |
|---|--|--|---------------------------------------|---|
| 3,4 4,4 1,4 2,4 3,4 4,4 1,4 2,4 3,4 4,4 1,4 2,4 3,4 | 10 10 11 11 11 12 12 12 12 13 13 | MO 17- 00:05 00:20 00:35 00:50 01:05 01:35 01:50 02:05 02:20 02:35 02:50 03:05 | F F F F F F F F | 464 462 470 469 463 458 462 463 461 464 467 469 474 |

SW13 053 Smplr Rpt

```
F
    13 03:20
                        481
4,4
1,4
    14 03:35
                F
                        487
    14 03:50
                F NL
2,4
3,4
    14 04:05
                F NL
4,4
    14 04:20
                F NL
1,4
    15 04:35
                F NL
2,4
    15 04:50
                F NL
3,4
    15 05:05
                F NL
4,4
    15 05:20
                F NL
1,4
    16 05:35
                F NL
2,4
    16 05:50
                F NL
    16 06:05
                F
3,4
                        482
4,4
    16 06:20
                F
                        481
1,4
                F
    17
        06:35
                        475
2,4
    17
        06:50
                F
                        476
                F
3,4
    17 07:05
                        471
                F
                        470
4,4
    17 07:20
    18 07:35
                F
1,4
                        470
                F
2,4
    18 07:50
                        469
                F
3,4
    18 08:05
                        463
                F
4,4
    18 08:20
                        459
1,4
    19 08:35
                F
                        461
                F
2,4
    19 08:50
                        463
                F
3,4
    19 09:05
                        463
4,4
    19 09:20
                F
                        459
                F
1,3
    20 09:35
                        463
    20 09:50
                 F
2,3
                        464
3,3
    20 10:05
                F
                        465
      10:20 MANUAL PAUSE
      10:20 PGM STOPPED 17-DEC
SOURCE E ==> ENABLE
SOURCE F ==> FLOW
 ERROR NL ==> NO LIQUID DETECTED!
```

Page 4

| *********** PROGRAM SETTINGS ********** |
|---|
| PROGRAM NAME: "PSNS015 " SITE DESCRIPTION: "PSNS015 " |
| UNITS SELECTED: LENGTH: ft |
| 24, 1000 ml BTLS 22 ft SUCTION LINE 18 ft SUCTION HEAD 0 RINSES, 0 RETRIES |
| ONE-PART PROGRAM |
| PACING: FLOW, EVERY 1 PULSES SAMPLE AT START |
| DISTRIBUTION: 4 SAMPLES/BOTTLE |
| VOLUME: 240 ml SAMPLES |
| ENABLE: NONE PROGRAMMED |
| ENABLE: ONCE ENABLED, STAY ENABLED SAMPLE AT ENABLE |
| ENABLE: 0 PAUSE & RESUMES |
| NO DELAY TO START |
| LIQUID DETECT ON NO RAIN GAGE |

-----NO YSI SONDE MASTER/SLAVE OFF BTL FULL DETECT OFF TIMED BACKLIGHT -----**EVENT MARK SENT DURING PUMP CYCLE** PUMP COUNTS FOR **EACH PURGE CYCLE:** 200 PRE-SAMPLE **AUTO POST-SAMPLE** -----I/O1= NONE I/O2= NONE I/O3= NONE -----**0 ANALOG OUTPUTS** NO PERIODIC **SERIAL OUTPUT** -----NO DIALOUT CONDITIONS SET ----SAMPLER ID# 2483481595 10:53 17-DEC-12 Hardware: B2 Software: 3.26 ****** SAMPLING RESULTS ******* SITE: PSNS015 PROGRAM: PSNS015 Program Started at 10:36 SA 15-DEC-12 Nominal Sample Volume = 240 ml COUNT TO SAMPLE BOTTLE TIME SOURCE ERROR LIQUID -----10:36 PGM DISABLED ----- SU 16-DEC-12 -----13:20 PGM ENABLED 1,4 1 13:20 Ε 817 F 2,4 1 13:34 829 F 3,4 1 13:49 811

4.4

1,4

2,4

1 14:04

2 14:19

2 14:34

F

F

F

797

800

809

| 4,4 11 00:04 F NM * 1,4 12 00:19 F 1703 2,4 12 00:34 F 878 | 3,4 4,4 1,4 3,4 4,4 4,4 4,4 4,4 4,4 4,4 4,4 4,4 4 | 2233334444555566666777778888999910101111 | 14:49 15:04 15:19 15:34 15:49 16:04 16:19 16:34 16:49 17:04 17:19 17:34 17:34 18:34 18:34 19:19 19:34 19:49 20:04 20:19 20:34 20:49 21:04 21:19 22:34 22:49 23:04 23:34 23:34 | F F F F F F F F F F F F F F F F F F F | 794 799 785 787 779 773 765 767 761 757 746 745 745 745 745 745 745 745 745 755 767 779 780 797 811 821 838 852 1301 854 |
|--|---|--|---|---------------------------------------|---|
| | 1,4 | 12 | 00:04 00:19 | F NM F | 1703 |

Page 3

```
F
     13 02:04
                        1034
4,4
1,4
     14 02:19
                 F
                        860
     14 02:34
                 F NM
2,4
3,4
     14 02:49
                 F
                        866
                 F
4,4
     14 03:04
                        865
1,4
     15 03:19
                 F
                        865
                 F
2,4
     15 03:34
                        877
                 F
3,4
     15 03:49
                        841
4,4
     15 04:04
                 F
                        830
                 F
1,4
     16 04:19
                        817
2,4
     16 04:34
                 F
                        807
                 F
     16 04:49
3,4
                        793
4,4
     16
        05:04
                 F
                        781
1,4
                 F
     17
        05:19
                        777
2,4
     17
        05:34
                 F
                        768
                 F
3,4
     17
        05:49
                        756
                 F
4,4
     17
        06:04
                        749
1,4
     18 06:19
                 F
                        739
        06:34
                 F
2,4
     18
                        737
                 F
3,4
     18 06:49
                        727
                 F
4,4
     18
        07:04
                        725
1,4
     19 07:19
                 F
                        721
                 F
2,4
     19 07:34
                        716
     19 07:49
                 F
3,4
                        714
4,4
     19 08:04
                 F
                        715
                 F
1,4
     20 08:19
                        708
     20
        08:34
                 F
2,4
                        713
     20
        08:49
                 F
                        710
3,4
                 F
4,4
     20
        09:04
                        715
                 F
1,4
     21
        09:19
                        714
                 F
2,4
     21
        09:34
                        721
3,4
     21
        09:49
                 F
                        727
4,4
    21 10:04
                 F
                        726
      10:10 MANUAL PAUSE
      10:10 PGM STOPPED 17-DEC
SOURCE E ==> ENABLE
SOURCE F ==> FLOW
 ERROR NM ==> NO MORE LIQUID!
```

| *********** PROGRAM SETTINGS ********** |
|--|
| PROGRAM NAME: "PSNS PB01 " SITE DESCRIPTION: "PSNS PB01 " |
| UNITS SELECTED: LENGTH: ft |
| 24, 1000 ml BTLS 30 ft SUCTION LINE 9 ft SUCTION HEAD 0 RINSES, 0 RETRIES |
| ONE-PART PROGRAM |
| PACING: FLOW, EVERY 1 PULSES SAMPLE AT START |
| DISTRIBUTION: 4 SAMPLES/BOTTLE |
| VOLUME: 240 ml SAMPLES |
| ENABLE: NONE PROGRAMMED |
| ENABLE: ONCE ENABLED, STAY ENABLED SAMPLE AT ENABLE |
| ENABLE: 0 PAUSE & RESUMES |
| NO DELAY TO START |
| |
| LIQUID DETECT ON NO RAIN GAGE |

| S' | W13 PB01 Smp |
|---|--------------|
| NO YSI SONDE | |
| MASTER/SLAVE OFF BTL FULL DETECT OFF TIMED BACKLIGHT | |
| EVENT MARK SENT DURING PUMP CYCLE | |
| PUMP COUNTS FOR EACH PURGE CYCLE: 200 PRE-SAMPLE AUTO POST-SAMPLE | |
| I/O1= NONE I/O2= NONE I/O3= NONE | |
| O ANALOG OUTPUTS NO PERIODIC SERIAL OUTPUT | |
| NO DIALOUT CONDITIONS SET | |
| SAMPLER ID# 2425546782 11:06 17 Hardware: B2 Software: 3.26 ************ SAMPLING RESULTS ***** SITE: PSNS PB01 PROGRAM: PSNS PB01 Program Started at 12:50 SA 15-DEC- Nominal Sample Volume = 240 ml COUNT | ***** |
| SAMPLE BOTTLE TIME SOURCE E | RROR LIQUID |
| 12:50 PGM DISABLED | Da 2 |

| 2.4 | 0 | 40.40 | _ | 700 |
|-----|----|-------|----------|-----|
| 3,4 | 2 | 12:18 | F | 783 |
| 4,4 | 2 | 12:33 | F | 783 |
| 1,4 | 3 | 12:48 | F | 783 |
| 2,4 | 3 | 13:03 | F | 783 |
| 3,4 | 3 | 13:18 | F | 789 |
| | | | | |
| 4,4 | 3 | 13:33 | F | 789 |
| 1,4 | 4 | 13:48 | F | 783 |
| 2,4 | 4 | 14:03 | F | 789 |
| 3,4 | 4 | 14:18 | F | 789 |
| 4,4 | 4 | 14:33 | F | 795 |
| 1,4 | 5 | 14:48 | F | 795 |
| | | | | |
| 2,4 | 5 | 15:03 | F | 795 |
| 3,4 | 5 | 15:18 | F | 795 |
| 4,4 | 5 | 15:33 | F | 789 |
| 1,4 | 6 | 15:48 | F | 789 |
| 2,4 | 6 | 16:03 | F | 789 |
| 3,4 | 6 | 16:18 | F | 789 |
| 4,4 | 6 | 16:33 | F | 795 |
| 1,4 | 7 | 16:48 | F | 789 |
| | | | | |
| 2,4 | 7 | 17:03 | F | 795 |
| 3,4 | 7 | 17:18 | F | 795 |
| 4,4 | 7 | 17:33 | F | 790 |
| 1,4 | 8 | 17:48 | F | 795 |
| 2,4 | 8 | 18:03 | F | 795 |
| 3,4 | 8 | 18:18 | F | 795 |
| 4,4 | 8 | 18:33 | F | 791 |
| 1,4 | 9 | 18:48 | F. | 794 |
| 2,4 | | 19:03 | | |
| | 9 | | F F | 795 |
| 3,4 | 9 | 19:18 | <u> </u> | 795 |
| 4,4 | 9 | 19:33 | F | 795 |
| 1,4 | 10 | 19:48 | F F | 789 |
| 2,4 | 10 | 20:03 | F | 791 |
| 3,4 | 10 | 20:18 | F | 791 |
| 4,4 | 10 | 20:33 | F | 795 |
| 1,4 | 11 | 20:48 | F | 795 |
| 2,4 | 11 | 21:03 | F | 801 |
| | | | | |
| 3,4 | 11 | 21:18 | F | 795 |
| 4,4 | 11 | 21:33 | F | 789 |
| 1,4 | 12 | 21:48 | F | 789 |
| 2,4 | 12 | 22:03 | F | 789 |
| 3,4 | 12 | 22:18 | F | 795 |
| 4,4 | 12 | 22:33 | F | 789 |
| 1,4 | 13 | 22:48 | F | 795 |
| 2,4 | 13 | 23:03 | F | 795 |
| 3,4 | 13 | 23:18 | F | 790 |
| | | | | |
| 4,4 | 13 | 23:33 | F | 795 |

| | | | | | SW1 |
|------------------------|----------|----------------|--------|-------------|-------|
| 1,4 | 14 | 23:48 | F | 790 | |
| 2.4 | 4 4 | MO 17-E | | 70 <i>E</i> | |
| 2,4 3,4 | 14 14 | 00:03 00:18 | F F | 795 795 | |
| 3, 4 4,4 | 14 | 00:18 | F | 795 | |
| 1,4 | 15 | 00:33 | F | 797 | |
| 2,4 | 15 | 01:03 | F | 795 | |
| 3,4 | 15 | 01:18 | F | 789 | |
| 4,4 | 15 | 01:33 | F | 791 | |
| 1,4 | 16 | 01:48 | F | 797 | |
| 2,4 | 16 | 02:03 | F | 789 | |
| 3,4 | 16 | 02:18 | F | 795 | |
| 4,4 | 16 | 02:33 | F | 797 | |
| 1,4 | 17 | 02:48 | F | 795 | |
| 2,4 | 17 | 03:03 | F | 801 | |
| 3,4 | 17 | 03:18 | F | 803 | |
| 4,4 | 17 | 03:33 | F | 797 | |
| 1,4 | 18 | 03:48 | F F | 795 708 | |
| 2,4 3,4 | 18 18 | 04:03 04:18 | F | 798 801 | |
| 3, 4 4,4 | 18 | 04:18 | F | 801 | |
| 1,4 | 19 | 04:48 | F | 795 | |
| 2,4 | 19 | 05:03 | F | 797 | |
| 3,4 | 19 | 05:18 | F | 795 | |
| 4,4 | 19 | 05:33 | F | 797 | |
| 1,4 | 20 | 05:48 | F | 795 | |
| 2,4 | 20 | 06:03 | F | 803 | |
| 3,4 | 20 | 06:18 | F | 795 | |
| 4,4 | 20 | 06:33 | F | 795 | |
| 1,4 | 21 | 06:48 | F | 791 | |
| 2,4 | 21 | 07:03 | F | 795 | |
| 3,4 | 21 | 07:18 | F | 795 | |
| 4,4 | 21 | 07:33 | F | 791 707 | |
| 1,4 | 22 | 07:48 | F | 797 | |
| 2,4 3,4 | 22 22 | 08:03 08:18 | F | 795 705 | |
| 3,4 4,4 | 22 | 08:33 | F F | 795 795 | |
| 1,4 | 23 | | F | 791 | |
| 2,4 | 23 | | F | 791 | |
| 3,4 | 23 | | F | 790 | |
| 4,4 | 23 | | F | 795 | |
| 1,3 | 24 | | F. | 795 | |
| 2,3 | 24 | | F | 797 | |
| 3,3 | 24 | | F | 794 | |
| | | 0:25 MA | | | |
| | 1 | 0:25 PG | M STO | PPED 1 | 7-DEC |

Page 4

SOURCE E ==> ENABLE SOURCE F ==> FLOW

National Weather Service National Headquarters National Weather Service

Area Forecast Discussion

Issued by NWS Seattle/Tacoma, WA

Current Version | Previous Version | Text Only | Print | Product List | Glossary Off Versions: 1234567891011121314151617181920212223242526272829303132333435

FXUS66 KSEW 161154 AFDSEW

AREA FORECAST DISCUSSION NATIONAL WEATHER SERVICE SEATTLE WA 354 AM PST SUN DEC 16 2012

.SYNOPSIS...A STRONG PACIFIC STORM WILL RACE TOWARD THE AREA TODAY. THIS SYSTEM WILL BRING THE POTENTIAL FOR DAMAGING WINDS ACROSS THE LOWLANDS AND HEAVY SNOW TO THE MOUNTAINS TONIGHT AND MONDAY. LOOK FOR SHOWERY WEATHER TO PREVAIL IN THE WAKE OF THE OCCLUDED FRONT THAT WILL MOVE ACROSS THE REGION MONDAY MORNING. THE SNOW LEVELS WILL ALSO FALL TO NEAR SEA LEVEL MONDAY NIGHT AS A COLDER AIR SETTLES OVER THE AREA. HIGHER PRESSURE ALOFT WILL SLOWLY BUILD IN FROM THE WEST DURING THE DAY TUESDAY.

CATTERED...MAINLY LIGHT...SHOWERS CONTINUED OVER THE FORECAST AREA EARLY THIS MORNING. LOOK FOR THE PRECIP TO FILL IN AND BECOME STEADY DURING THE DAY IN ADVANCE OF A STRONG LOW PRESSURE SYSTEM.

THE STRONG SYSTEM DUE TO IMPACT THE PACIFIC NORTHWEST WAS STILL WELL OFFSHORE. THE SURFACE LOW ASSOCIATED WITH THIS SYSTEM IS EXPECTED TO RAPIDLY DEEPEN TO NEAR 975 MB AS IT RACES EAST DURING THE DAY TODAY. THERE WAS STILL SOME DISAGREEMENT IN THE MODELS CONCERNING THE STRENGTH AND TIMING OF THIS FEATURE BUT THEY WERE STARTING TO COME INTO BETTER AGREEMENT. THE OPERATIONAL NAM WAS STILL THE OUTLIER. IT MUCH FASTER THAN THE OTHER MODELS...SO DECIDED TO LEAN TOWARD THE GFS AND ECMWF SOLUTIONS IN REGARDS TO THE TIMING.

WITH THAT IN MIND...ANTICIPATE STRONG...POSSIBLY DAMAGING...WINDS TO DEVELOP OVER THE COAST LATE TONIGHT AHEAD OF THE OCCLUDED FRONT. THE ONT WILL QUICKLY MOVE EAST ACROSS THE AREA EARLY MONDAY MORNING. DUE TO THE UNCERTAINTY IN THE TRACK OF THE LOW...HAVE CHOSEN TO KEEP THE WATCH UP FOR ALL OF THE LOWLANDS EXCEPT THE CENTRAL COAST.

CONFIDENCE OF A HIGH WIND EVENT FOR THE COAST WAS RELATIVELY
HIGHER...SO THE WATCH WAS UPGRADED TO A WARNING. IF THE LOW TRACKS
ACROSS THE PUGET SOUND AS SOME OF THE MODEL INDICATED...WINDS OVER
PARTS OF THE NORTH INTERIOR MIGHT END UP STAYING BELOW ADVISORY CRITERIA. IF THE BENT BACK OCCLUSION MOVE EAST ACROSS THE STRAIT OF JUAN DE FUCA...THERE MAY BE BRIEF HIGH WIND WESTERLIES OVER PARTS OF THE STRAIT OF JUAN DE FUCA AND POSSIBLY WHIDBEY ISLAND AS IT PASSES.

HEAVY SNOW IS STILL ANTICIPATED IN THE MOUNTAINS FROM THIS UPCOMING SYSTEM. THE CASCADES WILL LIKELY RECEIVE ANOTHER 1 TO 3 FEET OF SNOW BY LATE IN THE DAY MON. CONFIDENCE WAS HIGH FOR THE CASCADES...SO
THE WINTER STORM WATCH WAS UPGRADED TO A WARNING. KEPT THE ADVISORY
GOING FOR THE OLYMPICS THROUGH TODAY AS SNOW WILL BE PICKING UP
THERE DURING THE DAY. ALSO...KEPT THE WATCH UP FOR THE OLYMPICS FOR TONIGHT AS AMOUNTS ARE EXPECTED TO BE LOWER.

THE MODELS WERE IN GOOD AGREEMENT THAT THE PRECIP WILL QUICKLY TAPER OFF MON MORNING ACROSS MUCH OF THE AREA. THE EXCEPTION WAS THE CASCADES WHERE LOCALLY HEAVY SNOW SHOWERS WILL CONTINUE THROUGHOUT MUCH OF THE DAY...ALTHOUGH THE INTENSITY WILL GRADUALLY WIND DOWN DURING THE AFTERNOON AS THE OROGRAPHIC FORCING WEAKENS.

THE SNOW LEVELS WILL PLUMMET TO NEAR SEA LEVEL TUE NIGHT...THUS IND SNOW LEVELS WILL PLUMMET TO NEAR SEA LEVEL TUE NIGHT...THUS ANTICIPATE THE PRECIP TO CHANGE OVER TO SNOW OR A RAIN/SNOW MIX ACROSS THE LOWLANDS...IF IS PRECIP FALLING. WILL NEED TO WATCH OUT FOR THE PUGET SOUND CONVERGENCE ZONE /PSCZ/ THAT WILL LIKELY DEVELOP LATE MORN MORNING OR EARLY MON AFTERNOON. AT THIS TIME...IT IS EXPECTED TO DEVELOP OVER ITS FAVORITE LOCATION...NEAR THE KING/SNOHOMISH COUNTY LINE. THERE WILL BE THE POTENTIAL FOR SIGNIFICANT SNOWFALL MON NIGHT THROUGH TUE MORNING ACROSS THOSE LOWLAND AREAS IMPACTED BY THE PSCZ.

ANTICIPATE WEATHER CONDITIONS TO GRADUALLY WIND DOWN DURING THE DAY TUE AS HIGHER $\underline{\tt PRES}$ ALOFT BEGINS BUILDING IN FROM THE WEST.

AN <u>UNSETTLED</u> WEATHER PATTERN WILL PREVAIL OVER THE REGION DURING THIS PERIOD. CONFIDENCE IN THE DETAILS WERE NOT VERY HIGH DUE TO SOME DISAGREEMENT IN THE MODELS AS WELL AS SOME LACK OF CONTINUITY IN THE MODELS.

FLOODING IS NOT EXPECTED ON AREA RIVERS THROUGH THE END OF THE WEEK.

.AVIATION...SCATTERED SHOWERS CONTINUE EARLY THIS MORNING IN WEAKENING ONSHORE FLOW. SOUTHERLY SURFACE WINDS WILL BE TURNING OFFSHORE LATER THIS MORNING AS A DEEPENING SURFACE LOW APPROACHES THE REGION. RAIN WILL SPREAD ONSHORE ONCE AGAIN AHEAD OF A STRONG FRONTAL SYSTEM TODAY. WINDS ALOFT WILL BECOME RATHER STRONG LATE THIS AFTERNOON WITH SOUTHERLY WINDS OF 50-60 KNOTS NEAR 5000 FEET EXPECTED BY 00Z.

KSEA...SOME SHORT-LIVED IMPROVEMENT IN CEILINGS EXPECTED LATER THIS MORNING AS DEVELOPING OFFSHORE GRADIENTS SCOUR OUT SOME LOW LEVEL MOISTURE. RAIN REDEVELOPING BY EARLY AFTERNOON WITH MVFR RETURNING AFTER 00Z. SLY SURFACE WINDS TURN OFFSHORE AFTER 18Z WITH E-SE WIND 10 TO 20 KNOTS WITH HIGHER GUSTS AFTER 00Z. STRONG POST-FRONTAL ONSHORE WIND SHIFT WILL BRING VERY GUSTY SW WIND AFTER 09Z MONDAY.

.MARINE...A STRONG FRONTAL SYSTEM WILL REACH THE AREA LATE TONIGHT WITH AN ASSOCIATED SURFACE LOW NEAR 977 MILLIBARS MOVING ONSHORE SOMEWHERE NEAR THE NORTH WASHINGTON COAST DURING THE EARLY HOURS OF MONDAY MORNING. I HAVE CONVERTED THE STORM WATCHES FOR THE COASTAL WATERS AND STRAIT OF JUAN DE FUCA INTO STORM WARNINGS. SUSTAINED WIND SPEEDS OVER THE COASTAL WATERS WILL BE IN THE 35 TO 45 KNOT RANGE...BUT THERE WILL BE HIGHER GUSTS NEAR 55 KNOTS AT TIMES. THE 00Z RUN OF THE 4KM UW-WRFGFS HAD LARGE SWATHS OF 50 TO 60 KNOT WIND GUSTS BOTH IMMEDIATELY AHEAD OF AND BEHIND THE SURFACE LOW OVER THE COASTAL WATERS AND STRAIT. THE TRACK OF THE SURFACE LOW FAVORS A STRONG WESTERLY SURGE BEHIND IT AS IT MOVES ONSHORE EARLY MONDAY MORNING. GALES ARE EXPECTED FOR ALL REMAINING WATERS BY EARLY MONDAY. MODELS CONTINUE TO SHOW A STRONG POST-FRONTAL GRADIENT OF +13 MB PDX-BLI 18Z MONDAY. THIS ALONG WITH THE NAM12 SHOWING A 6HR ISALLOBARIC BULLSEYE OF +15MB OVER THE NORTH SOUND SHOULD PRODUCE A FULL GALE OVER PUGET SOUND.

THE DEEP LOW MONDAY MORNING WILL LIKELY GIVE A STORM SURGE OF A COUPLE FOOT TIDAL ANOMALY SO TIDAL OVERFLOW IS LIKELY DURING HIGH TIDE MONDAY MORNING IN THE INTERIOR WATERS AROUND 8 AM. THE TIMING IS DIFFERENT ON THE COAST WHERE THE FIRST HIGH TIDE AROUND 3AM WILL HAVE SE GALES AND THE WAVES STILL BUILDING...THEN LOW TIDE MAY COINCIDE WITH THE HIGHEST TIDAL ANOMALY WHICH HELPS FOR AWHILE. THE MONDAY AFTERNOON HIGH TIDE WILL SEE HIGH SURF OF 23 TO 28 FEET COASTAL AREAS, 27

88

.SEW WATCHES/WARNINGS/ADVISORIES..

WA...<u>WINTER WEATHER ADVISORY</u> IN EFFECT FOR THE OLYMPICS UNTIL 6 PM THIS EVENING.

WINTER STORM WARNING IN EFFECT FOR THE CASCADES FROM 6 PM THIS EVENING TO 6 PM MONDAY.

HIGH WIND WARNING IN EFFECT FOR THE CENTRAL COAST FROM MIDNIGHT TONIGHT UNTIL 10 AM MONDAY.

WINTER STORM WATCH IN EFFECT FOR THE OLYMPICS FROM THIS EVENING THROUGH MONDAY MORNING.

HIGH WIND WATCH IN EFFECT FOR THE LOWLANDS...EXCEPT THE CENTRAL COAST...FROM LATE TONIGHT THROUGH MONDAY MORNING.

COASTAL ${\color{red} {\text{FLOOD}}}$ WATCHES ARE IN EFFECT FOR THE COAST AND INTERIOR

PZ...STORM WARNINGS ARE IN EFFECT FOR THE COASTAL WATERS AND STRAIT OF JUAN DE FUCA.

ALE WARNINGS ARE IN EFFECT FOR THE REMAINING WATERS FROM MIDNIGHT TONIGHT TIL 3 PM MONDAY.

SMALL CRAFT ADVISORY IN EFFECT FOR ROUGH GRAYS HARBOR BAR CONDITIONS UNTIL 4 AM TUESDAY.

& &

\$\$

WWW.WEATHER.GOV/SEATTLE

FOR THE GRAPHICAL AFD...VISIT WWW.WEATHER.GOV/SEATTLE/GAFD/LATEST WEBAFD.HTML

National Weather Service National Weather Service National Headquarters 1325 East West Highway Silver Spring, MD 20910 Incorrect Region Format! Web Master's E-mail: NWS Internet Services Team

Page last modified: Jul 16th, 2012 21:28 UTC

Disclaimer Credits Glossarv

Privacy Policy About Us Career Opportunities **PAST WEATHER**

N



Local forecast by "City, St" or ZIP code

HOME

Go Enter location ...

Location Help

NWS Wants Your Comments on a Proposed Alternative to Simplify Winter Haza

WEATHER SAFETY

Are you confused about our terms "Watch," "Warning" and "Advisory"? NWS wants your feed alternative to communicating winter hazard messages. The goal of this demonstration is to ex our messages to improve public understanding. We will create live examples of alternative me

Read More...

BREMERTON WA

FORECAST



Overcast 3°C

Humidity 81% Wind Speed S 10 MPH Barometer 29.74 in Dewpoint 32°F (0°C) Visibility 10.00 mi

Last Update on 16 Dec 8:15 am PST

Current conditi **Bremerto** (KPWT) Lat: 47.5 Lc

More Local Share |

WEDNESDA'

TODAY

TONIGHT

MONDAY

MONDAY NIGHT

50%



TUESDAY





TUESDAY

NIGHT

INFORMATION CENTER

Rain Likely High: 42 °F

Heavy Rain High: 42 °F

100%

Heavy Rain Low: 40 °F

100%

100% Showers

High: 42 °F

Chance Rain/Snow Low: 35 °F

Chance Rain/Snow High: 40 °F

Chance Rain Low: 36 °F

HAZARDOUS WEATHER CONDITIONS

Coastal Flood Watch

High Wind Watch

NWS Sea **Point Forec**

7-DAY FORECAST

Rain. The rain could be heavy at times. High near 42. South southe **Today** of precipitation is 100%.


Tonight Rain. The rain could be heavy at times. Low around 40. South wind high as 20 mph. Chance of precipitation is 100%.

Showers, mainly before 4pm. High near 42. Windy, with a south sol Monday gusts as high as 48 mph. Chance of precipitation is 100%.

A chance of rain showers before 10pm, then a chance of snow shown Monday lowering to 0 feet. Mostly cloudy, with a low around 35. Breezy, with Night mph, with gusts as high as 30 mph. Chance of precipitation is 50%.

than a half inch possible.


Tuesday



| -Day Foleca | st for Latitude 47.36 in and Longitude 122.62 w (Elev. 0) |
|--------------------|--|
| | A chance of snow showers before 10am, then a chance of rain sho sunny, with a high near 40. Southwest wind 18 to 21 mph, with gust precipitation is 30%. New snow accumulation of less than a half inc |
| Tuesday Night | A 50 percent chance of rain. Mostly cloudy, with a low around 36. |
| Wednesday | Rain likely. Cloudy, with a high near 42. Chance of precipitation is 7 |
| Wednesday Night | Rain likely. Cloudy, with a low around 39. |
| Thursday | Rain likely. Mostly cloudy, with a high near 44. |
| Thursday Night | Showers likely. Mostly cloudy, with a low around 38. |
| Friday | A chance of showers. Mostly cloudy, with a high near 44. |



HOURLY



Showers likely. Mostly cloudy, with a low around 39. **Friday Night**

Rain likely. Mostly cloudy, with a high near 45. Saturday

ADDITIONAL FORECASTS AND INFORMATION


ZONE AREA FORECAST FOR SEATTLE/BREMERTON AREA, WA

Forecast Discussion **Printable Forecast Text Only Forecast**

Hourly Weather Graph **Tabular Forecast Quick Forecast**

Air Quality Forecasts International System of Units **About Point Forecasts** Forecast Weather Table Interface

NATION DATABA



ACTIVE ALERTS

Warnings By State Excessive Rainfall and Winter Weather Forecasts River Flooding Latest Warnings Thunderstorm/Tornado Outlook Hurricanes Fire Weather Outlooks **UV Alerts** Drought Space Weather **NOAA** Weather Radio **NWS CAP Feeds**

PAST WEATHER

Past Weather **Climate Monitoring** Heating/Cooling Days Monthly Temps Records

CURRENT CONDITIONS

Radar **Climate Monitoring** River Levels **Observed Precipitation** Surface Weather Upper Air Marine and Buoy Reports **Snow Cover** Satellite **Space Weather**

FORECAST

Marine

Local Forecast Severe Weather **Current Outlook Maps** Drought Fire Weather Fronts/Precipitation Maps **Current Graphical Forecast** Maps Rivers

INFORMATION CENTER

Space Weather Tsunami For Developers Storm Spotters Cooperative Observers GIS Water **Forecast Models** Aviation Fire Weather Climate Marine Daily Briefing Facts and Figures

WEATHER SAFETY


NOAA Weather Radio Federal Emergency Management Agency (FEMA) **Red Cross** Damage/Fatality/Injury **Statistics** Air Quality Ultra Violet Radiation Winter Weather Floods **Rip Currents** Severe Weather **Tornadoes Thunderstorms** Hurricanes Lightning Heat StormReady **Brochures**

NEWS

Newsroom Social Med **Events** Pubs/Broch

EDUCATI

NOAA Ecol NOAA Edu Glossarv JetStream **NWS Train**i **NOAA Libra** Play Time f For Studen For Teache Brochures Other Links




Forecast For Lat/Lon: 47.5620/-122.6230 (Elev. 0 ft) Bremerton WA


Forecast Created at: 8am PST Dec 16, 2012

Custom Weather Forecast Table

| | Sun Dec 16 | | | | | | | | | Mon Dec 17 | | | | | | | Tue Dec 18 |
|---------------------|---------------------|-------------|--------|-----------------|-----------|-------------|---------|--|-------------|------------|---------------------------------|---------|---------------------------|----------|----------|----------|------------------|
| Weather | Likely Rain Rain | | | Ra | Rain Rain | | | Rain Numero Rain Rain Showers Shower | | ain | Rain | | Chance Snow Showers | | | | |
| Daily-Temp | | | | High 4 Low 3 | | | | | | | High 42 Low 40 | | | | | | Low 35 |
| Chance of Precip | 60 | 0% | 10 | 0% | 10 | 0% | 10 | 0% | 10 | 0% | 65 | % | 50 | 0% | 50 | % | |
| Precip | 0.0 | 0.02" 0.25" | | | 0.4 | 0.46" 0.20" | | | 0.09" 0.02" | | 0. | 0.01" | | 0.01" | | | |
| 12-hr Snow Total | 0" | | | | 0" | | | 0" | | | Trc | | | | | | |
| 3-Hour | | | 10am | | | • | 10pm | | | | | | | | | 1am | |
| Temp | 38 | 38 | 40 | 42 | 42 | 41 | 41 | 41 | 40 | 40 | 41 | 42 | 42 | 39 | 37 | 37 | |
| Cloudiness | | | | | | | 100% | | | | | | | 56% | 56% | | |
| Dewpoint | 32 | 33 | 37 | 39 | 39 | 39 | 39 | 38 | 38 | 39 | 39 | 40 | 38 | 39 | 37 | 36 | |
| Relative Humdity | 79% | 82% | 89% | 89% | 89% | 93% | 93% | 89% | 92% | 94% | 94% | 93% | 86% | 100% | 100% | 96% | |
| Wind | SW 12 | SW 12 | S 9 | S 14 | S 14 | SE 12 | S 14 | S 14 | SW 29 | S 28 | S 28 | S 35 | SW 23 | SW 23 | SW 20 | SW 20 | |
| Snow Level (ft) | 1292 | 1292 | 1160 | 1160 | 1557 | 1557 | 2797 | 2797 | 3152 | 3152 | 1264 | 1264 | 520 | 520 | 0 | 0 | |




SW13 Radar Image



Radar Image (from Langley Hill) captured near height of SW13, 12/16/2012 (1505)

SW13 Satellite Image



Satellite image captured during SW13 in the early morning hours of 12/17/12, as the vortex of the rain event passes through the Puget Sound region and southern British Columbia (infrared western US 4KM view).